

271

16214

Dependent Resurvey, Portion of Subdivisional Lines,
T. 23 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

A hemlock, 20 ins. diam., bears S. 60° W., 187 lks. dist., with scribe marks T23S R9W S20 BT visible on partially healed blaze.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, alder, maple, chinquapin, and yew; undergrowth, hazel, rhododendron, huckleberry, willow, salmonberry, blackberry, salal, Oregon grape, and fern.

N. 1° 42' E., on the W. bdy. of sec. 21.

Ascend 30 ft. over SE. slope, through heavy young timber and dense undergrowth.

4.10

Point for the NW. cor. of sec. 21 only, at record distance in latitude from the cor. of secs. 16 and 20 only, and at record distance in departure from the $\frac{1}{4}$ sec. cor. of secs. 16 and 21; there is no remaining evidence of the original corner. This point falls in gravelled road, 25 lks. wide, bears N. 85° E. and W.

Set an iron post, 28 ins. long, 2½ ins. diam., 34 ins. in the ground, the top 6 ins. below the surface of the road, with brass cap mkd.

S 16
T 23 S
R 9 W
S 21

1977

from which

A fir, 18 ins. diam., bears S. 15½° E., 69½ lks. dist., mkd. T23S R9W S21 BT.

No other suitable trees available within limits.

From the $\frac{1}{4}$ sec. cor. of secs. 16 and 21, determined at record bearing and distance from the remains of an original bearing tree:

A sawed fir stump, 70 ins. diam., bears N. 72° E., 25 lks. dist., with scribe marks $\frac{1}{4}$ S16 BT visible on bark blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 23 S R 9 W
$\frac{1}{4}$ S 16
S 21

1977

from which new bearing trees

A fir, 15 ins. diam., bears N. 27½° E., 97 lks. dist., mkd. $\frac{1}{4}$ S16 BT.

A fir, 13 ins. diam., bears S. 45° W., 14 lks. dist., mkd. $\frac{1}{4}$ S21 BT.