

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 23 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

A fir, 18 ins. diam., bears S. 79° E., 45 lks. dist., mkd. T23S R9W S29 BT.

A fir, 15 ins. diam., bears S. 22½° W., 9 lks. dist., mkd. T23S R9W S30 BT.

A fir, 15 ins. diam., bears N. 33½° W., 26 lks. dist., mkd. T23S R9W S19 BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, alder, maple, chinquapin, and yew; undergrowth; hazel, rhododendron, huckleberry, willow, salmonberry, blackberry, salal, Oregon grape, and fern.

From the cor. of secs. 29 and 32 only, determined at record bearing and distance from the remains of an original bearing tree:

A sawed fir stump, 35 ins. diam., bears S. 69° W., 23 lks. dist., with illegible scribe marks visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 23 S R 9 W  
S 29 | S 33  
S 32 |  
1977

from which a new bearing tree

A fir, 52 ins. diam., bears N. 75½° W., 177 lks. dist., mkd. T23S R9W S29 BT.

No other suitable trees available within limits.

N. 1° 27' W., on the E. bdy. of sec. 29.

Descend 20 ft. over N. slope, through scattered timber and dense undergrowth.

0.20 Creek, 2 lks. wide, course S. 80° W.; asc. 10 ft. over SW. slope.

2.11 True point for the closing cor. of secs. 28 and 33, hereinafter described.

Ascend 475 ft. over SW. slope.

20.75 Gravelled road, 20 lks. wide, bears N. 65° E. and S. 65° W.

24.65 Ridge, bears E. and W.; desc. 240 ft. over NW. slope.

37.49 Point for the ¼ sec. cor. of sec. 29 only, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.