

Dependent Resurvey, Portion of Subdivisional Lines,
T. 23 S., R. 9 W., Willamette Meridian, Oregon

| | |
|----------------|--|
| CHAINS 9.50 | Spur, slopes N.; desc. 300 ft. over steep NW. slope. |
| 19.35 | Point for the E 1/16 sec. cor. of secs. 28 and 33. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> $\begin{array}{r} \text{E } 1/16 \text{ } \frac{\text{S } 28}{\text{S } 33} \\ 1977 \end{array}$ </div> from which A fir, 4 ins. diam., bears N. 21° W., 57 lks. dist., mkd. X BT. A fir, 6 ins. diam., bears S. 36½° E., 71½ lks. dist., mkd. E 1/16 S33 BT. Descend 595 ft. over broken W. slope. |
| 38.70 | The ¼ sec. cor. of secs. 28 and 33, perpetuated and recorded by Louis B. Praher, Registered Land Surveyor No. 308, in 1966, and further perpetuated by the Douglas County Surveyor, in 1975, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. <div style="text-align: center;"> COUNTY SURVEYORS T 23 S ¼ $\frac{\text{S } 28}{\text{S } 33}$ R 9 W 1975 OFFICE </div> from which the remains of the original bearing trees A fir snag, 30 ins. diam., bears N. 15° E., 47 lks. dist., with scribe marks BT visible on opened blaze. A root hole, bears S. 69° W., 27 lks. dist., with a down fir alongside, size indeterminate, with scribe marks ¼ visible on opened blaze. and the remains of bearing trees mkd. by Praher A sawed fir stump, 48 ins. diam., bears N. 52° E., 36 lks. dist., with an iron spike driven in base. A sawed fir stump, 38 ins. diam., bears N. 29° W., 110 lks. dist., with iron spike driven in base. No other suitable trees available within limits. <hr style="width: 20%; margin: auto;"/> S. 88° 24' W., beginning new measurement. Descend 30 ft. over SW. slope. |
| 1.50 | Creek, 1 lk. wide, course SW.; asc. 70 ft. along S. slope. |
| 19.60 | Spur, slopes S. 40° W.; desc. 380 ft. over SW. slope. |