

16223

Dependent Resurvey, Portion of Subdivisional Lines,
T. 23 S., R. 9 W., Willamette Meridian, Oregon

CHAINS
2.33

Point for the closing cor. of secs. 29 and 32, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 23 S R 9 W
S 30 | S 29
 | S 32 CC
1977

from which

A maple, 6 ins. diam., bears N. 24½° E., 80½ lks. dist., mkd. T23S R9W S29 CC BT.

A fir, 4 ins. diam., bears S. 77¾° E., 55 lks. dist., mkd. X BT.

Set a 5 ft. steel fence post alongside iron post.

Ascend 90 ft. over SW. slope.

11.00 Spur, slopes N. 30° W.; desc. 200 ft. over NE. slope.

19.42 Point for the S 1/16 sec. cor. of secs. 29 and 30.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

S 1/16
S 30 | S 29
1977

from which

A fir, 4 ins. diam., bears S. 17° W., 53 lks. dist., mks. X BT.

No other suitable trees available within limits.

Set a 5 ft. steel fence post alongside iron post.

Descend 350 ft. over NE. slope.

36.50 Creek, 10 lks. wide, course S. 80° W.; asc. 10 ft. over S. slope.

38.84 The ¼ sec. cor. of secs. 29 and 30, perpetuated and recorded by the Douglas County Surveyor, in 1939, and further perpetuated by the County Surveyor, in 1973, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS
T 23 S R 9 W
¼
S 30 | S 29
1973
OFFICE

from which the remains of an original bearing tree

A sawed fir stump, 36 ins. diam., bears N. 30° E., 19 lks. dist., with scribe marks ¼ S29 BT visible on open blaze. (Record, N. 20° E.)

and bearing trees mkd. by the County Surveyor, in 1973