

Dependent Resurvey, Portion of Subdivisional Lines,
T. 23 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
	<p>A fir, 8 ins. diam., bears N. $3\frac{1}{2}^{\circ}$ E., 28$\frac{1}{2}$ lks. dist., with illegible scribe marks visible on partially healed blaze.</p> <p>A fir, 11 ins. diam., bears S. 49° W., 82 lks. dist., with illegible scribe marks visible on partially healed blaze.</p> <hr/> <p>N. $3^{\circ} 11'$ W., beginning new measurement.</p> <p>Ascend 530 ft. over SE. slope, through scattered timber and dense undergrowth.</p>
1.20	Dirt road, 15 lks. wide, bears E. and W.
29.40	Gravelled road, 20 lks. wide, bears E. and W.
30.60	Ridge, bears N. 85° E. and S. 85° W.; desc. 260 ft. over NE. slope.
32.00	Dirt road, 15 lks. wide, bears NW. and SE.
39.40	The cor. of secs. 19, 20, 29, and 30.
	<p>Land, mountainous. Soil, rocky clay. Timber, fir, hemlock, cedar, alder, maple, chinquapin, and yew; undergrowth, hazel, rhododendron, huckleberry, blackberry, willow, salmonberry, salal, Oregon grape, and fern.</p>
	<p>From the cor. of secs. 29 and 32 only.</p> <p>N. $85^{\circ} 10'$ W., bet. secs. 29 and 32.</p> <p>Descend 20 ft. over SW. slope, through scattered timber and dense undergrowth.</p>
0.75	Creek, 2 lks. wide, course S. 75° W.; asc. 20 ft. over SE. slope.
3.97	<p>The $\frac{1}{4}$ sec. cor. of secs. 29 and 32, perpetuated and recorded by Louis B. Prahar, Registered Land Surveyor No. 308, in 1966, monumented with an iron rod, $\frac{5}{8}$ in. diam., firmly set, projecting 24 ins. above ground, from which the remains of the original bearing tree:</p> <p>A root hole, bears S. 79° W., 33 lks. dist., with a down fir alongside, 36 ins. diam., no marks visible.</p> <p>and the remains of bearing trees mkd. by Prahar</p> <p>A chinquapin, 17 ins. diam., bears N. $21\frac{1}{4}^{\circ}$ W., 38 lks. dist., with a steel spike at base.</p> <p>A chinquapin snag, 20 ins. diam., bears S. 15° W., 33 lks. dist., with a steel spike at base.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, directly over iron rod, with brass cap mkd.</p>