

18225

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 23 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

T 23 S R 9 W

$$\frac{1}{2} \frac{S 29}{S 32}$$

1977

from which a new bearing tree

A fir, 5 ins. diam., bears S.  $46\frac{1}{2}^{\circ}$  E., 61 lks.  
dist., mkd. X BT.

N.  $89^{\circ} 34'$  W., beginning new measurement.

Ascend 395 ft. over broken SE. slope.

24.50 Enter logged area, edge bears N. and S.

34.50 Spur, slopes N.  $10^{\circ}$  E.; desc. 195 ft. over W. slope.

38.54 Intersect the E. bdy. of sec. 30.

The closing cor. of secs. 29 and 32, hereinbefore  
described.

From this point, the cor. of secs. 30 and 31 only, bears  
S.  $0^{\circ} 34'$  E., 2.33 chs. dist., hereinbefore described.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, alder, maple, chinquapin,  
and yew; undergrowth, hazel, rhododendron, huckleberry,  
blackberry, willow, salmonberry, salal, Oregon grape,  
and fern.

From the cor. of secs. 30 and 31 only.

S.  $89^{\circ} 38'$  W., bet. secs. 30 and 31.

Descend 435 ft. over NW. slope, across logged area,  
through light undergrowth.

19.55 Creek, 2 lks. wide, course N.  $25^{\circ}$  E.; asc. 15 ft. over  
E. slope.

20.00 Point for the E  $1/16$  sec. cor. of secs. 30 and 31.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins.  
in the ground, with brass cap mkd.

$$E \frac{1}{16} \frac{S 30}{S 31}$$

1977

from which

A hemlock, 9 ins. diam., bears N.  $11^{\circ}$  E.,  $44\frac{1}{2}$  lks.  
dist., mkd. E  $1/16$  S30 BT.

A hemlock, 10 ins. diam., bears S.  $70\frac{1}{2}^{\circ}$  W., 53  
lks. dist., mkd. E  $1/16$  S31 BT.

Ascend 320 ft. over NE. slope.

27.40 Spur, slopes N.; desc. 250 ft. over NW. slope.