

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 23 S., R. 9 W., Willamette Meridian, Oregon

CHAINS  
40.00

The  $\frac{1}{4}$  sec. cor. of secs. 30 and 31, perpetuated and recorded by the Douglas County Surveyor, in 1970, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS

T 23 S

$\frac{1}{4}$  S 30

S 31

R 9 W

1970

OFFICE

from which the remains of an original bearing tree

A sawed fir stump, 16 ins. diam., bears N. 28° E., 12 lks. dist., with scribe marks  $\frac{1}{4}$  S visible on partially healed blaze.

and the remains of bearing trees mkd. by the County Surveyor

A chinquapin snag, 8 ins. diam., bears N. 85° E., 13 lks. dist., with scribe marks BT visible on partially healed blaze.

A sawed fir stump, 34 ins. diam., bears S. 42° W., 36 lks. dist., with healed blaze.

and a new bearing tree

A fir, 8 ins. diam., bears N. 33 $\frac{1}{2}$ ° W., 87 $\frac{1}{2}$  lks. dist., mkd.  $\frac{1}{4}$  S30 BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, alder, maple, chinquapin, and yew; undergrowth, hazel, rhododendron, huckleberry, willow, salmonberry, blackberry, salal, Oregon grape, and fern.

From the cor. of secs. 19, 20, 29, and 30.

N. 88° 09' W., bet. secs. 19 and 30.

Ascend 105 ft. over NE. slope, through heavy timber and dense undergrowth.

1.50 Spur, slopes N. 35° E.; desc. 30 ft. over NW. slope.

5.70 Ravine, drains N. 25° E.; asc. 115 ft. over NE. slope.

9.20 Ridge, bears N. 45° W. and S. 45° E.; desc. 305 ft. over SW. slope.

28.00 Creek, 1 lk. wide, course S. 35° W.; asc. 75 ft. over SE. slope.

31.50 Spur, slopes S. 20° W.; desc. 130 ft. over SW. slope.

39.40 Point for the  $\frac{1}{4}$  sec. cor. of secs. 19 and 30, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.