

16227

Dependent Resurvey, Portion of Subdivisional Lines,
T. 23 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

*Fd. OK 5/91
M113-3A A 4B*

T 23 S R 9 W
¼ S 19
S 30
1977

from which

A fir, 10 ins. diam., bears N. 24° W., 72 lks.
dist., mkd. ¼ S19 BT.

A fir, 6 ins. diam., bears S. 23½° E., 39½ lks.
dist., mkd. ¼ S30 BT.

Descend 25 ft. over SW. slope.

41.00 Creek, 1 lk. wide, course S. 5° E.; asc. 40 ft. over
SE. slope.

43.60 Spur, slopes S.; desc. 30 ft. over SW. slope.

45.30 Bottom of descent, slopes S.; asc. 25 ft. over SE. slope.

46.55 Spur, slopes S.; desc. 55 ft. over SW. slope.

50.20 Bottom of descent, slopes S. 40° W.; asc. 20 ft. over
SE. slope.

52.20 Top of ascent, slopes S.; desc. 90 ft. over SW. slope.

60.40 Bottom of descent, slopes S.; asc. 25 ft. along S. slope.

77.97 The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of
the Tp., perpetuated and recorded by the Douglas County
Surveyor, in 1957, based on testimony from adjacent
landowners, and is accepted as the best available
evidence of the original corner position, monumented
with an iron post, 2 ins. diam., firmly set, projecting
4 ins. above ground, with brass cap mkd.

*Fd. OK 5/91
M113-3A A 4B*

COUNTY SURVEYORS
R T 23 S R
10 24 | 19 9
W 25 | 30 W
1957
OFFICE

from which bearing trees mkd. by the County Surveyor

A white fir, 15 ins. diam., bears S. 69½° E., 38
lks. dist., with healed blaze.

A white fir, 22 ins. diam., bears S. 64½° W., 65
lks. dist., with healed blaze.

A white fir, 8 ins. diam., bears N. 89° W., 58
lks. dist., with healed blaze.

and the remains of a bearing tree of which I have no
record

A sawed fir stump, 28 ins. diam., bears N. 63½° E.,
77 lks. dist., with scribe marks T23S R9W S BT
visible on open blaze.

and a new bearing tree

A white fir, 12 ins. diam., bears N. 56½° E., 65½
lks. dist., mkd. T23S R9W S19 BT.