

16233

354

Corrective Dependent Resurvey of a
Portion of the East Boundary,
T. 32 S., R. 7 W., Willamette Meridian, Oregon

CHAINS 39.16	<p>The $\frac{1}{4}$ sec. cor. of secs. 19 and 24, on the E. bdy. of the Tp., perpetuated and recorded by Lloyd D. Smith, Registered Land Surveyor No. 1101, in 1978, monumented with a galvanized iron pipe, $1\frac{1}{2}$ ins. diam., firmly set, projecting 2 ins. above ground, with bronze cap mkd.</p>
	<p>OREGON STATE BOARD OF FORESTRY T 32 S R 7 W $\frac{1}{4}$ R 6 W S 24 S 19 1978 RS 1101</p>
	<p>from which the remains of bearing trees mkd. by Byars</p>
	<p>A burned and shattered fir stump, 52 ins. diam., bears S. 48° E., 48 lks. dist., with axe work visible at top and a chaining notch visible at bottom of opened blaze. The center of blaze has been removed. (Record, 45 lks.)</p>
	<p>A burned out root crown, approximately 48 ins. diam., bears N. 52° W., 30 lks. dist.</p>
	<p>and bearing trees mkd. by Smith</p>
	<p>A madrone, 10 ins. diam., bears S. 72° E., 32 lks. dist., with scribe marks $\frac{1}{4}$ S19 BT RS1101 visible on open blaze.</p>
	<p>A fir, 28 ins. diam., bears S. 35° W., 37 lks. dist., with scribe marks $\frac{1}{4}$ S24 BT RS1101 visible on opened blaze.</p>
	<p>From this point, the $\frac{1}{4}$ sec. cor. of secs. 19 and 24, erroneously reestablished by Popken and Carlson, in 1976, bears N. $6^\circ 53'$ W., 0.32 chs. dist., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 4 ins. above ground, mkd. and witnessed as described in the official record of the 1975-76 resurvey.</p>
	<p>I remove the iron post, and destroy the scribe marks on the bearing trees.</p>
	<p>N. $0^\circ 12'$ E., beginning new measurement.</p>
	<p>Descend 5 ft. along E. slope.</p>
0.75	<p>Head of ravine, drains S. 70° E.; asc. 125 ft. over SE. slope.</p>
9.35	<p>Spur, slopes S. 50° E.; desc. 130 ft. over NE. slope.</p>
18.75	<p>Ravine, drains E.; asc. 45 ft. over SE. slope.</p>
20.08	<p>The N $\frac{1}{16}$ sec. cor. of secs. 19 and 24, established and recorded by Lloyd D. Smith, Registered Land Surveyor No. 1101, in 1978, monumented with a galvanized iron pipe, $1\frac{1}{2}$ ins. diam., firmly set, projecting 12 ins. above ground, and in a mound of stone, 4 ft. base, to top, with bronze cap mkd.</p>
	<p>OREGON STATE BOARD OF FORESTRY N $\frac{1}{16}$ S 24 S 19 1978 RS 1101</p>