

18235

386

Corrective Dependent Resurvey of a
Portion of the East Boundary,
T. 32 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

A fir, 28 ins. diam., bears N. $74\frac{1}{2}^{\circ}$ E., 131 $\frac{1}{2}$ lks. dist., with scribe marks T32S R6W S18 BT RS1101 visible on partially healed blaze.

A fir, 20 ins. diam., bears S. 24° E., 73 lks. dist., with scribe marks T32S R6W S19 BT visible on partially healed blaze. This tree was mkd. by Popken and Carlson, in 1976.

A fir, 15 ins. diam., bears S. 63° W., 17 lks. dist., with scribe marks T32S R7W S24 BT visible on partially healed blaze. This tree was also mkd. on SE. face by Popken and Carlson, in 1976.

A fir, 38 ins. diam., bears N. 1° W., 92 $\frac{1}{2}$ lks. dist., with scribe marks T32S R7W S13 BT visible on partially healed blaze.

From this point, the cor. of secs. 13, 18, 19, and 24, erroneously reestablished by Popken and Carlson, in 1976, bears S. $3^{\circ} 21'$ W., 0.355 chs. dist., monumented with an iron post, 2 $\frac{1}{2}$ ins. diam., firmly set, projecting 8 ins. above ground, and in a mound of stone, 2 ft. base, to top, mkd. and witnessed as described in the official record of the 1975-76 resurvey.

I remove the iron post, and destroy the scribe marks on the NE., SW., and NW. bearing trees.

Corner is located on a steep, rocky, live oak covered SE. slope.

Land, mountainous.

Soil, rocky clay, with rock outcroppings in N $\frac{1}{2}$ mile. Timber, fir, pine, oak, madrone, cedar, and dogwood; undergrowth, poison oak, arrowwood, hazel, manzanita, fern, and young timber.

N. $0^{\circ} 13'$ E., bet. secs. 13 and 18.

Ascend 190 ft. over rocky broken SE. slope, through medium timber and dense undergrowth.

9.35 Spur, slopes S. 70° E.; asc. 275 ft. over SE. slope.

19.65 Point for the S $1/16$ sec. cor. of secs. 13 and 18.

From this point, the S $1/16$ sec. cor. of secs. 13 and 18, erroneously established by Popken and Carlson, in 1976, bears S. $3^{\circ} 21'$ W., 0.27 chs. dist., monumented with an iron post, 2 $\frac{1}{2}$ ins. diam., firmly set, projecting 6 ins. above ground, and in a mound of stone, 3 ft. base, to top, mkd. and witnessed as described in the official record of the 1975-76 resurvey.

I remove the iron post, and at the true corner point

Reset the iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 6 ins. in the ground, to solid rock, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

S $1/16$
S 13 | S 18
1976
1979