

Corrective Dependent Resurvey of a
Portion of the East Boundary,
T. 32 S., R. 7 W., Willamette Meridian, Oregon

CHAINS																
	<p>from which bearing trees mkd. by Popken and Carlson</p> <p>A fir, 16 ins. diam., bears S. $80\frac{1}{2}^{\circ}$ E., $36\frac{1}{2}$ lks. dist., with scribe marks S 1/16 S18 BT visible on partially healed blaze.</p> <p>A fir, 20 ins. diam., bears S. 13° W., 54 lks. dist., with scribe marks S 1/16 S13 BT visible on partially healed blaze.</p> <p>Ascend 165 ft. over SE. slope.</p>															
31.25	<p>Rocky ridge dividing Cow Creek and Middle Creek drainages, bears N. 40° E. and S. 40° W.; also enter heavy timber and moderate undergrowth, edge bears same; desc. 235 ft. over NW. slope.</p>															
39.30	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 18, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>From this point, the $\frac{1}{4}$ sec. cor. of secs. 13 and 18, erroneously reestablished by Popken and Carlson, in 1976, bears S. $3^{\circ} 21'$ W., 0.18 chs. dist., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 4 ins. above ground, mkd. and witnessed as described in the official record of the 1975-76 resurvey.</p> <p>I remove the iron post, and at the true corner point</p> <p>Reset the iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 32 S</p> <p>$\frac{1}{4}$</p> <table style="margin: auto;"> <tr> <td>R 7 W</td> <td> </td> <td>R 6 W</td> </tr> <tr> <td>S 13</td> <td> </td> <td>S 18</td> </tr> <tr> <td colspan="3" style="text-align: center;">1976</td> </tr> <tr> <td colspan="3" style="text-align: center;">1979</td> </tr> </table> </div> <p>from which bearing trees mkd. by Popken and Carlson</p> <p>A fir, 15 ins. diam., bears S. $58\frac{1}{2}^{\circ}$ E., $15\frac{1}{2}$ lks. dist., with scribe marks $\frac{1}{4}$ S18 BT visible on partially healed blaze.</p> <p>A fir, 12 ins. diam., bears S. 49° W., 58 lks. dist., with scribe marks $\frac{1}{4}$ S13 BT visible on partially healed blaze.</p> <p>Descend 780 ft. over NW. slope, changing to steep N. slope.</p>	R 7 W		R 6 W	S 13		S 18	1976			1979					
R 7 W		R 6 W														
S 13		S 18														
1976																
1979																
67.75	<p>Bottom of descent, slopes W.; asc. 60 ft. over SW. slope.</p>															
73.25	<p>Spur, slopes N. 60° W.; desc. 205 ft. over N. slope.</p>															
78.60	<p>The cor. of secs. 7, 12, 13, and 18, perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1965, redescribed by Popken and Carlson, in 1975-76, monumented with an iron pipe, $1\frac{1}{2}$ ins. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 32 S</p> <table style="margin: auto;"> <tr> <td>R7W</td> <td>S 12</td> <td> </td> <td>S 7</td> <td>R6W</td> </tr> <tr> <td></td> <td>S 13</td> <td> </td> <td>S 18</td> <td></td> </tr> <tr> <td colspan="5" style="text-align: center;">1965</td> </tr> </table> </div>	R7W	S 12		S 7	R6W		S 13		S 18		1965				
R7W	S 12		S 7	R6W												
	S 13		S 18													
1965																