

359

16238

Corrective Dependent Resurvey of a
Portion of the Subdivisional Lines,
T. 32 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
	<p>I remove the iron post, and at the true corner point</p> <p>Reset the iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">E 1/16 $\frac{S\ 13}{S\ 24}$ 1976 1979</p> <p>from which bearing trees mkd. by Popken and Carlson</p> <p>A fir, 14 ins. diam., bears N. 5½° E., 85½ lks. dist., with scribe marks E 1/16 S13 BT visible on partially healed blaze.</p> <p>A fir, 15 ins. diam., bears S. 29¾° E., 42½ lks. dist., with scribe marks E 1/16 S24 BT visible on partially healed blaze.</p> <p>Descend 660 ft. over steep rocky SW. slope.</p>
37.80	Creek, 1 lk. wide, course S. 25° E.; asc. 30 ft. over SE. slope, through medium timber, along N. edge of logged area.
38.58	<p>Point for the ¼ sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>From this point, the ¼ sec. cor. of secs. 13 and 24, erroneously reestablished by Popken and Carlson, in 1976, bears S. 3° 08' W., 0.18 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, mkd. and witnessed as described in the official record of the 1975-76 resurvey.</p> <p>I remove the iron post, and at the true corner point</p> <p>Reset the iron post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, and in a mound of stone, 2½ ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 32 S R 7 W ¼ $\frac{S\ 13}{S\ 24}$ 1976 1979</p> <p>from which bearing trees mkd. by Popken and Carlson</p> <p>A fir, 8 ins. diam., bears N. 2½° W., 5 lks. dist., with scribe marks ¼ S13 BT visible on partially healed blaze.</p> <p>A fir, 11 ins. diam., bears S. 10° W., 87 lks. dist., with scribe marks ¼ S24 BT visible on partially healed blaze.</p> <p>Ascend 545 ft. over steep rocky SE. slope.</p>
60.70	Ridge, bears NE. and SW.; desc. 470 ft. over broken NW. slope.
77.16	The cor. of secs. 13, 14, 23, and 24, reestablished at proportionate distance by Popken and Carlson, in 1976, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.