

378

16242

Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

Beginning at the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

T 30 S R 7 W
S 35 | S 36
S 2 | S 1
T 31 S
1977
1969

from which bearing trees mkd. by Jelley, in 1977

A cedar, 25 ins. diam., bears N. 24½° E., 75 lks. dist., with scribe marks T30S R7W S36 BT visible on open blaze.

A cedar, 18 ins. diam., bears S. 41° E., 59 lks. dist., with scribe marks T31S R7W S1 BT visible on open blaze.

A cedar, 7 ins. diam., bears S. 58½° W., 48½ lks. dist., with scribe marks T31S R7W S2 BT visible on open blaze.

A cedar, 11 ins. diam., bears N. 59½° W., 71 lks. dist., with scribe marks T30S R7W S35 BT visible on open blaze.

N. 4° 16' W., bet. secs. 35 and 36, marking and blazing the true line.

Descend 15 ft. over NW. slope, through scattering timber and dense undergrowth.

1.50 Creek, 5 lks. wide, course N. 40° E.; asc. 10 ft. over SE. slope.

3.15 Spur, slopes N. 50° E.; desc. 50 ft. over NE. slope.

16.50 Cow Creek, 150 lks. wide, course S. 30° E.; asc. 45 ft. over SW. slope.

20.10 Top of ascent, slopes SW.; continue over nearly level land.

20.505 Point for the S 1/16 sec. cor. of secs. 35 and 36.

Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, with brass cap mkd.

S 1/16
S 35 | S 36
1977

from which

A pine, 7 ins. diam., bears S. 87½° E., 113½ lks. dist., mkd. S 1/16 S36 BT.

A basalt boulder, 5 x 5 x 3 ft. above ground, bears S. 26½° W., 31 lks. dist., mkd. X BO on top.

Continue over nearly level land.