

Dependent Resurvey, Portion of Subdivisional Lines, **16243**
T. 30 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
21.10	Cow Creek Road, asphalt surfaced, 40 lks. wide, bears N., curving N. 20° E., and S., curving S. 30° E.
31.50	Same road, 40 lks. wide, bears N. 20° W. and S. 20° E.
33.00	Southern Pacific Railroad, bears N. 20° W. and S. 20° E.; asc. 40 ft. over SW. slope.
36.60	Dirt road, 20 lks. wide, bears N. 20° W. and S. 20° E.
41.01	The ½ sec. cor. of secs. 35 and 36, perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1964, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.
	COUNTY SURVEYORS OFFICE <i>FO OK BY SMALLEY</i> T 30 S ½ S 35 S 36 R 7 W 1964 <i>7/92 M 112-52</i>
	from which the remains of an original bearing tree
	A white oak snag, 18 ins. diam., bears N. 85° W., 48 lks. dist., no marks visible.
	and bearing trees mkd. by Tracy
	A white oak, 8 ins. diam., bears S. 21¾° E., 33 lks. dist., with fragmentary scribe marks visible on partially open blaze.
	A white oak, 9 ins. diam., bears S. 62¾° W., 26 lks. dist., with fragmentary scribe marks visible on partially open blaze.
	—————
	N. 1° 52' W., beginning new measurement.
	Ascend 75 ft. over SW. slope.
11.20	Ravine, drains W.; asc. 15 ft. over SW. slope.
14.00	Ravine, drains S. 35° W.; asc. 180 ft. over SE. slope.
19.77	Point for the N 1/16 sec. cor. of secs. 35 and 36.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	N 1/16 S 35 S 36 1976
	from which
	A fir, 5 ins. diam., bears N. 31° E., 12 lks. dist., mkd. N 1/16 S36 BT.
	A fir, 19 ins. diam., bears N. 24° W., 65 lks. dist., mkd. N 1/16 S35 BT.
	Ascend 35 ft. over SW. slope.
20.85	Spur, slopes S. 70° W.; desc. 190 ft. over NW. slope.
33.30	Ravine, drains N. 10° W.; asc. 95 ft. over SW. slope.