

380

16244

Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 7 W., Willamette Meridian, Oregon

CHAINS
39.54

The cor. of secs. 25, 26, 35, and 36, perpetuated and recorded by Arthur R. Evans, Registered Engineer No. 2741, in 1953, and further perpetuated by James W. Byron, Deputy County Surveyor, in 1964, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

FD. OK BY SMALLEY
7/92 M 112-52

COUNTY SURVEYORS OFFICE

T 30 S
S 26 | S 25
S 35 | S 36
R 7 W
1964

from which the remaining original bearing tree

A fir, 35 ins. diam., bears N. 76° W., 72 lks. dist., with healed blaze.

and bearing trees mkd. by Evans

A live oak, 10 ins. diam., bears N. 21° E., 15 lks. dist., with scribe marks T30S R7W S25 BT visible on open blaze.

A live oak, 9 ins. diam., bears S. 64° E., 18 lks. dist., with scribe marks R7W S36 visible on partially open blaze.

A live oak, 10 ins. diam., bears S. 2° E., 25 lks. dist., with scribe marks T30S R7W S35 visible on open blaze.

and a bearing tree mkd. by Jelley and Akin, in 1971-73

An oak, 11 ins. diam., bears S. 11½° W., 35 lks. dist., with scribe marks T30S R7W S35 BT visible on open blaze.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, oak, maple, myrtle, alder, and chinquapin; undergrowth, salal, Oregon grape, vine maple, rhododendron, hazel, poison oak, and fern.

From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., perpetuated and recorded by James W. Byron, County Surveyor, in 1962, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 30 S
S 34 | S 35 R
S 3 | S 2 7
T 31 S W
1962

from which the remains of the original bearing trees

A pine snag, 37 ins. diam., bears N. 65¾° E., 217 lks. dist., no marks visible.

A pine, 25 ins. diam., bears S. 87¼° W., 32 lks. dist., with fragmentary scribe marks visible on open blaze.