

Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 7 W., Willamette Meridian, Oregon

18247

CHAINS
37.77

The cor. of secs. 26, 27, 34, and 35, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1962, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 30 S
S 27 | S 26
S 34 | S 35
R 7 W
1962

from which the remains of an original bearing tree

A fir snag, 24 ins. diam., bears N. 75° W., 23 lks. dist., no marks visible.

and the remains of bearing trees mkd. by Byron

A fir snag, 15 ins. diam., bears S. 49½° E., 127 lks. dist., with healed blaze.

A live oak, 25 ins. diam., bears S. 64½° W., 26 lks. dist., with scribe marks S34 CS BT visible on partially open blaze.

A live oak, 8 ins. diam., bears N. 20° W., 82½ lks. dist., with scribe marks S27 CS BT visible on partially open blaze.

No other suitable trees available within limits.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, maple, oak, madrone, alder, live oak, myrtle, and chinquapin; undergrowth, salal, vine maple, Oregon grape, rhododendron, hazel, and poison oak.

From the cor. of secs. 25, 26, 35, and 36.

S. 88° 25' W., bet. secs. 26 and 35.

Descend 105 ft. over W. slope, through heavy timber and dense undergrowth.

2.75 Salt Creek, 4 lks. wide, course S. 20° E.; asc. 230 ft. over E. slope.

6.70 Spur, slopes S. 20° E.; desc. 265 ft. over SW. slope.

19.395 Point for the E 1/16 sec. cor. of secs. 26 and 35.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

E 1/16 $\frac{S\ 26}{S\ 35}$
1977

from which

A fir, 14 ins. diam., bears N. 42¾° E., 41 lks. dist., mkd. E 1/16 S26 BT.

A pine, 25 ins. diam., bears S. 79¾° E., 50 lks. dist., mkd. E 1/16 S35 BT.