

Subdivision of Section 35, T. 30 S., R. 7 W., **16253**
Willamette Meridian, Oregon

CHAINS 1.90	Cow Creek, 200 lks. wide, course S. 10° E.; asc. 70 ft. over NE. slope.
6.90	Creek, 3 lks. wide, course N. 40° E.; asc. 285 ft. over SE. slope.
19.92	The SE 1/16 sec. cor. of sec. 35. Ascend 570 ft. over SE. slope.
39.86	The center S 1/16 sec. cor. of sec. 35.
	From the center W 1/16 sec. cor. of sec. 35. N. 1° 12' W., on the N. and S. center line of the NW¼ of sec. 35. Descend 70 ft. over NW. slope.
4.25	Spur, slopes NW.; desc. 425 ft. over NE. slope.
16:15	Cow Creek, 60 lks. wide, course E.; asc. 20 ft. over S. slope.
18.80	Cow Creek Road, asphalt surfaced, 40 lks. wide, bears E. and W.
19.11	Point for the NW 1/16 sec. cor. of sec. 35, at intersection with the E. and W. center line of the NW¼. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. NW 1/16 S 35 1977 from which An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 68° E., 38 lks. dist., with brass cap mkd. NW 1/16 S35 RM 1977, and an arrow pointing to the corner. An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 72½° W., 22 lks. dist., with brass cap mkd. NW 1/16 S35 RM 1977, and an arrow pointing to the corner. No suitable trees available within limits. Ascend 390 ft. over S. slope.
19.70	Southern Pacific Railroad, bears E. and W.
30.85	Spur, slopes S. 45° W.; desc. 50 ft. along W. slope.
38.21	The W 1/16 sec. cor. of secs. 26 and 35.
	From the center N 1/16 sec. cor. of sec. 35. S. 89° 02' W., on the E. and W. center line of the NW¼ of sec. 35. Descend 35 ft. over NW. slope.