

365

Corrective Dependent Resurvey of a Portion of
the North Boundary,
T. 31 S., R. 7 W., Willamette Meridian, Oregon

16257

CHAINS

Beginning at the cor. of Tps. 30 and 31 S., Rs. 6 and 7 W., monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

*FD OK 7/92
SMALLEY M 112-52*

T 30 S		
R 7 W		R 6 W
S 36		S 31
S 1		S 6
T 31 S		
1965		

*FD OK 6/88
H. JOHNSTONE
M 106-52*

from which the remains of the original bearing trees

A decayed madrone stump, 24 ins. diam., bears N. 36° E., 148 lks. dist., no marks visible.

A madrone, 16 ins. diam., bears N. 45° W., 212 lks. dist., no marks visible.

and bearing trees mkd. by John H. Markham, Registered Engineer, No. 2880, in 1961

A black oak, 8 ins. diam., bears N. 72° E., 39½ lks. dist., with healed blaze.

A fir, 11 ins. diam., bears South, 81 lks. dist., with healed double blaze.

A fir, 9 ins. diam., bears S. 85° W., 21 lks. dist., with healed blaze.

A fir, 7 ins. diam., bears N. 15° W., 13½ lks. dist., with healed double blaze.

and a bearing tree mkd. by John M. Jelley, in 1965

A fir, 17 ins. diam., bears S. 11° E., 76 lks. dist., with healed blaze.

S. 89° 59' W., bet. secs. 1 and 36, marking and blazing the true line.

Ascend 545 ft. over NE. slope, through moderate timber and dense undergrowth.

18.40 Top of ascent, slopes N.; desc. 95 ft. over NW. slope.

24.25 Ravine, drains N. 20° W.; asc. 35 ft. over NE. slope.

30.00 Spur, slopes N. 60° W.; desc. 320 ft. over NW. slope.

38.20 Ravine, drains N. 30° W.; asc. 35 ft. over N. slope.

40.74 Point for the ¼ sec. cor. of secs. 1 and 36, at proportionate distance; there is no remaining evidence of the original corner.

From this point, the ¼ sec. cor. of secs. 1 and 36, erroneously reestablished by Jelley, in 1969, bears N. 61° 20' W., 0.085 chs. dist., set, mkd. and witnessed as described in the official record.

I remove the iron post, destroy the marks on the bearing trees, and at the proportionate corner point

Reset the iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.