

18260

Corrective Dependent Resurvey of a Portion of
the North Boundary,
T. 31 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

From this point, the E 1/16 sec. cor. of secs. 2 and 35, erroneously established by Jelley, in 1969, bears N. 42° 20' W., 0.075 chs. dist., set, mkd. and witnessed as described in the official record.

I remove the iron post, destroy the marks on the bearing trees, and at the corner point

Reset the iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$E \frac{1}{16} \frac{S \ 35}{S \ 2}$$

1977

1969

from which

A fir, 10 ins. diam., bears N. 30° W., 40½ lks. dist., mkd. E 1/16 S35 BT.

A fir, 4 ins. diam., bears S. 8° W., 61½ lks. dist., mkd. X BT.

Ascend 440 ft. over broken E. slope.

40.74

Point for the ¼ sec. cor. of secs. 2 and 35, at proportionate distance; there is no remaining evidence of the original corner.

From this point, the ¼ sec. cor. of secs. 2 and 35, erroneously reestablished by Jelley, in 1969, bears N. 48° 01' E., 0.04 chs. dist., set, mkd. and witnessed as described in the official record.

I remove the iron post, destroy the marks on the bearing trees, and at the proportionate corner point

Reset the iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 30 S

$$\frac{1}{4} \frac{S \ 35}{S \ 2}$$

T 31 S R 7 W

1977

1969

from which

A fir, 5 ins. diam., bears N. 12½° E., 65 lks. dist., mkd. ¼ S35 BT.

A fir, 8 ins. diam., bears S. 34½° W., 88 lks. dist., mkd. ¼ S2 BT.

Ascend 170 ft. over broken E. slope.

48.00

Ridge, bears N. and S.; desc. 345 ft. over SW. slope.

51.60

Dirt road, 15 lks. wide, bears N. and S.

61.20

Ravine, drains S. 40° W.; asc. 45 ft. over SE. slope.

69.45

Spur ridge, bears N. 60° E. and S. 60° W., and same dirt road, 15 lks. wide, bears same as spur ridge; desc. 85 ft. over NW. slope.