

122

Dependent Resurvey of a Portion of the
Seventh Standard Parallel South
(South Boundary, T. 32 S., R. 7 W.)
Willamette Meridian, Oregon

18267

CHAINS

Beginning at the standard cor. of secs. 35 and 36, monumented with an iron post, 2½ ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.

S C
T 32 S R 7 W
S 35 | S 36
1969

from which the remains of the original bearing trees

A sawed fir stump, 30 ins. diam., bears N. 30° E., 14 lks. dist., no marks visible.

A sawed fir stump, 32 ins. diam., bears S. 10° E., 19 lks. dist., with scribe marks 1 BT visible on bark blaze.

A root hole, bears N. 46° W., 37 lks. dist.

and bearing trees mkd. by Milner L. Larson, Registered Engineer No. 3642, in 1967

A fir, 17 ins. diam., bears N. 28° E., 23 lks. dist., with healed blaze.

A live oak, 17 ins. diam., bears South, 48½ lks. dist., with scribe marks 3642 BT visible on partially healed blaze.

A fir, 20 ins. diam., bears N. 34½° W., 27 lks. dist., with healed blaze.

N. 89° 00' W., on the S. bdy. of sec. 35, marking and blazing the true line.

Descend 15 ft. over nearly level creek bottom, through scattered timber and dense undergrowth.

2.65 Cow Creek, 120 lks. wide, course S. 10° W.; asc. 325 ft. over SE. slope.

4.25 Southern Pacific Railroad tracks, track bears N. 10° E. and S. 10° W.

6.00 Asphalt surfaced road, 30 lks. wide, bears N. 20° E. and S. 20° W.

6.95 Gravelled road, 25 lks. wide, bears N. 20° E. and S. 20° W.

27.85 Spur, slopes S.; desc. 15 ft. over W. slope.

28.94 From this point, a point established and recorded by Claude E. Masters, Registered Land Surveyor No. 457, in 1971, bears South, 0.08 chs. dist., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 3 ins. above ground, from which:

A madrone, 8 ins. diam., bears S. 8° E., 24½ lks. dist., with scribe marks ¼ S2 RS 457 BT visible on partially healed double blaze.

A madrone, 10 ins. diam., bears S. 64° W., 40 lks. dist., with scribe marks ¼ S2 RS 457 BT visible on partially healed blaze.