

18268

Dependent Resurvey of a Portion of the
Seventh Standard Parallel South
(South Boundary, T. 32 S., R. 7 W.)
Willamette Meridian, Oregon.

CHAINS	
39.48	<p>Descend 110 ft. over W. slope.</p> <p>Point for the standard $\frac{1}{4}$ sec. cor. of sec. 35, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S C T 32 S R 7 W <u>$\frac{1}{4}$ S 35</u> 1975</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears N. 10° E., $119\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S35 SC BT.</p> <p style="padding-left: 40px;">A madrone, 14 ins. diam., bears N. $30\frac{1}{2}^\circ$ W., $13\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S35 SC BT.</p>
52.85	<p>Descend 175 ft. over W. slope.</p> <p>Creek, 5 lks. wide, course S. 20° W.; asc. 110 ft. along S. slope.</p>
54.65	<p>Dirt road, 15 lks. wide, bears N. 20° E. and S. 20° W.</p>
63.00	<p>Top of ascent, slopes S.; desc. 30 ft. along S. slope.</p>
68.71	<p>True point for the closing cor. of secs. 2 and 3, T. 33 S., R. 7 W., hereinafter described.</p>
78.96	<p>Descend 75 ft. over SW. slope, along N. edge of pasture.</p> <p>The standard cor. of secs. 34 and 35, perpetuated and recorded by Norman D. Price, Registered Land Surveyor No. 33, in 1954, from the original bearing trees which are no longer in existence, monumented with an iron pipe, 2 ins. diam., firmly set, projecting 6 ins. above ground, with brass washer mkd. RS 33, from which bearing trees mkd. by Price:</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears N. $9\frac{1}{2}^\circ$ E., 68 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A madrone, 15 ins. diam., bears N. $24\frac{3}{4}^\circ$ W., $27\frac{1}{2}$ lks. dist., with scribe marks T32S R7W S34 SC RS33 BT visible on bark blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, directly over iron pipe, with brass cap mkd.</p> <p style="text-align: center;">S C T 32 S R 7 W <u>S 34 S 35</u> 1975</p>
	<p>Corner is located in a fence line, fence extends E. and W.</p> <p>Land, rolling. Soil, clay and sandy loam.</p>