

124

Dependent Resurvey of a Portion of the
Seventh Standard Parallel South
(South Boundary, T. 32 S., R. 7 W.)
Willamette Meridian, Oregon

18269

CHAINS	Timber, fir, pine, oak, madrone, chinquapin, and alder; undergrowth, poison oak, Oregon grape, salal, hazel, manzanita, and chaparral.
	N. 89° 59' W., on the S. bdy. of sec. 34.
	Descend 75 ft. over SW. slope, along N. edge of pasture.
4.25	Barbed wire fence, extends N. 40° W. and S. 40° E., leave pasture.
5.00	Asphalt surfaced road, 36 lks. wide, bears N. 40° W. and S. 40° E.; enter heavy timber and dense undergrowth.
9.15	Southern Pacific Railroad tracks, track bears N. 60° W. and S. 60° E.
11.80	Right bank of Cow Creek, 75 lks. wide, bears E. and W., course West; thence along right bank.
21.50	Leave right bank of Cow Creek, bears E. and S. 70° W., course S. 70° W.; asc. 20 ft. over SE. slope.
25.35	Top of ascent, slopes S.; desc. 20 ft. along S. slope.
39.19	Point for the standard $\frac{1}{4}$ sec. cor. of sec. 34, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	S C T 32 S R 7 W $\frac{1}{4}$ S 34 1975
	from which
	A fir, 9 ins. diam., bears N. 38° E., 102 lks. dist., mkd. $\frac{1}{4}$ S34 SC BT.
	A fir, 6 ins. diam., bears N. 60° W., 187 $\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S34 SC BT.
	Descend 20 ft. along right bank of Cow Creek.
44.95	Right bank of Cow Creek, 75 lks. wide, bears S. 70° E. and N. 70° W., course N. 70° W.; asc. 20 ft. over NE. slope.
51.95	Creek, 2 lks. wide, course N. 30° E.; asc. 175 ft. over NE. slope.
56.40	Dirt road, 20 lks. wide, bears N. and S.
61.45	Top of ascent, slopes N.; desc. 20 ft. over W. slope.
62.70	Ravine, drains N. 20° E.; asc. 30 ft. over E. slope.
66.10	Spur, slopes N.; desc. 40 ft. over W. slope.
68.10	Ravine, drains N.; asc. 10 ft. over E. slope.
68.59	True point for the closing cor. of secs. 3 and 4, T. 33 S., R. 7 W., hereinafter described.