

16270

Dependent Resurvey of a Portion of the
Seventh Standard Parallel South
(South Boundary, T. 32 S., R. 7 W.)
Willamette Meridian, Oregon

CHAINS									
69.00	Ascend 5 ft. over E. slope.								
73.70	Spur, slopes N.; desc. 80 ft. over broken NW. slope.								
74.50	Dirt road, 20 lks. wide, bears N. 20° E. and S. 20° W.								
77.30	Creek, 2 lks. wide, course N. 10° E.; asc. 20 ft. over NE. slope.								
78.38	Top of ascent, slopes N.; desc. 10 ft. over NW. slope.								
	The standard cor. of secs. 33 and 34, perpetuated and recorded by Norman D. Price, Registered Land Surveyor No. 33, in 1954, monumented with an iron pipe, 2 ins. diam., firmly set, projecting 6 ins. above ground, with brass washer mkd. RS 33, from which the remaining original bearing tree:								
	A cedar, 24 ins. diam., bears N. 55° E., 56 lks. dist., with healed blaze.								
	and a bearing tree mkd. by Price								
	A cedar, 18 ins. diam., bears N. 34½° W., 15½ lks. dist., with healed blaze.								
	At the corner point								
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over iron pipe, with brass cap mkd.								
	<p>FD. OK 795 BY TEMPLIN M 122-53</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td>S</td><td>C</td></tr> <tr><td>T 32</td><td>S R 7 W</td></tr> <tr><td>S 33</td><td>S 34</td></tr> <tr><td colspan="2">1975</td></tr> </table>	S	C	T 32	S R 7 W	S 33	S 34	1975	
S	C								
T 32	S R 7 W								
S 33	S 34								
1975									
	Land, mountainous. Soil, rocky clay. Timber, fir, pine, cedar, maple, alder, oak, and madrone; undergrowth, poison oak, manzanita, ceanothus, vine maple, salal, and Oregon grape.								
	Dependent Resurvey of a Portion of the Subdivisional Lines T. 33 S., R. 7 W., Willamette Meridian, Oregon								
	(Restoring the survey by William H. Byars, U. S. Deputy Surveyor, in 1882)								
	From the cor. of secs. 2, 3, 10, and 11, perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1968, monumented with an iron pipe, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.								
	<p>COUNTY SURVEYORS OFFICE</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T 33</td><td>S R 7 W</td></tr> <tr><td>S 3</td><td>S 2</td></tr> <tr><td>S 10</td><td>S 11</td></tr> <tr><td colspan="2">1968</td></tr> </table>	T 33	S R 7 W	S 3	S 2	S 10	S 11	1968	
T 33	S R 7 W								
S 3	S 2								
S 10	S 11								
1968									
	from which the remains of the original bearing trees								
	A maple snag, 15 ins. diam., bears N. 33° E., 87 lks. dist., no marks visible. (Record, N. 32° E., 92 lks.)								