

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 33 S., R. 7 W., Willamette Meridian, Oregon

| CHAINS |   |
|--------|---|
| 13.15  | Asphalt surfaced road, 35 lks. wide, bears N. 60° W. and S. 80° E.  |
| 14.00  | Corner of fences, extending N. and W., thence along E. edge of pasture.   |
| 25.775 | <p>The closing cor. of secs. 2 and 3, perpetuated and recorded by George J. Wenderoth, Deputy County Surveyor, in 1965, monumented with an iron pipe, 1½ ins. diam., firmly set, extending 5 ins. above ground, with brass cap mkd. COUNTY SURVEYORS OFFICE R7W 2 3 T33S 1965 DEP LS 5, from which the remains of the original bearing trees:</p> <p>A madrone snag, 13 ins. diam., bears S. 24° E., 6 lks. dist., with illegible scribe marks visible in negative on overgrowth.</p> <p>A clump of chinquapin, bears S. 47° W., 12 lks. dist.</p> <p>A chinquapin, 22 ins. diam., bears N. 45° W., 22 lks. dist., with healed blaze.</p> <p>and bearing trees mkd. by Wenderoth</p> <p>A chinquapin, 22 ins. diam., bears S. 83° E., 43½ lks. dist., with scribe marks S2 CS BT visible on partially healed double blaze.</p> <p>A chinquapin, 16 ins. diam., bears S. 18¾° E., 26 lks. dist., with scribe marks S2 CS BT visible on partially healed double blaze.</p> <p>This point now becomes an amended monument.</p> <p>Corner is located at corner of fences, extending S. and W.</p> |
| 25.83  | <p>Intersect the Seventh Standard Parallel South.</p> <p>True point for the closing cor. of secs. 2 and 3.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 32 S R 7 W</p> <p>    S 35</p> <p>    S 3   S 2</p> <p>T 33 S R 7 W</p> <p>    C C</p> <p>    1975</p> </div> <p>from which the remains of the original bearing trees now bear</p> <p>A madrone snag, 13 ins. diam., bears S. 13½° E., 11 lks. dist.</p> <p>A clump of chinquapin, bears S. 28° W., 17 lks. dist.</p> <p>A chinquapin, 22 ins. diam., bears N. 58° W., 19½ lks. dist.</p> <p>and bearing trees mkd. by Wenderoth</p>   |