

16276

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 33 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
	<p>No other suitable trees available within limits.</p> <p>Land, mountainous. Soil, rocky clay. Timber, fir, pine, cedar, oak, madrone, alder, and chinquapin; undergrowth, poison oak, hazel, salal, manzanita, huckleberry, vine maple, and Oregon grape.</p>
	<p>N. 0° 08' E., bet. secs. 3 and 4.</p> <p>Ascend 270 ft. over broken SE. slope, through heavy timber and dense undergrowth.</p>
12.85	Spur, slopes E.; desc. 15 ft. over NE. slope.
16.90	Bottom of descent, slopes E.; asc. 330 ft. over SE. slope, changing to broken E. slope.
43.91	<p>The <math>\frac{1}{2}</math> sec. cor. of secs. 3 and 4, reestablished by proportionate measurement by Norman D. Price, Registered Land Surveyor No. 33, in 1954, monumented with an iron pipe, <math>1\frac{1}{2}</math> ins. diam., firmly set, projecting 12 ins. above ground, with brass washer mkd. RS 33. There is no remaining evidence of the original corner; therefore, this position is accepted as the corner, from which bearing trees mkd. by Price:</p> <p style="padding-left: 40px;">A fir, 29 ins. diam., bears S. 64° E., 10 lks. dist., with healed double blaze.</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears N. 89° W., 9 lks. dist., with healed double blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, directly over iron pipe, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 33 S R 7 W</p> <p><math>\frac{1}{2}</math></p> <p>S 4   S 3</p> <p>1975</p> </div> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears N. 32<math>\frac{1}{2}</math>° W., 40 lks. dist., mkd. <math>\frac{1}{4}</math> S4 BT.</p>
	<p>N. 0° 10' E., beginning new measurement.</p> <p>Ascend 5 ft. along E. slope.</p>
0.70	Spur, slopes N. 50° E.; desc. 815 ft. over N. slope.
22.10	<p>The N <math>\frac{1}{16}</math> sec. cor. of secs. 3 and 4, established and recorded by Norman D. Price, Registered Land Surveyor No. 33, in 1954. This position is accepted as the corner and is monumented with an iron pipe, <math>\frac{3}{4}</math> in. diam., firmly set, projecting 10 ins. above ground, with brass washer mkd. RS 33, from which the remains of bearing trees mkd. by Price:</p> <p style="padding-left: 40px;">A tan oak, 16 ins. diam., bears S. 66° E., 71<math>\frac{1}{2}</math> lks. dist., with scribe marks N <math>\frac{1}{16}</math> S3 RS33 BT visible on partially healed double blaze.</p>