

Dependent Resurvey, Portion of Subdivisional Lines,
T. 33 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

A fir snag, 13 ins. diam., bears N. 40° W., 25
lks. dist., with scribe marks N 1/16 S4 RS33 BT
visible on partially healed double blaze.

N. 0° 05' E., beginning new measurement.

Descend 390 ft. over N. slope, through scattered timber
and dense undergrowth, across old logged area.

11.50 Ravine, drains N. 60° E.; asc. 20 ft. over SE. slope.

15.60 Spur, slopes N. 70° E.; desc. 230 ft. over NE. slope.

26.50 Intersect the Seventh Standard Parallel South.

True point for the closing cor. of secs. 3 and 4.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 32 S R 7 W
S 34
S 4 | S 3
C C
T 33 S R 7 W
1975

from which the remains of bearing trees mkd. by Price

A fir, 42 ins. diam., bears S. 51¼° E., 80 lks.
dist., with healed blaze.

A chinquapin snag, 11 ins. diam., bears S. 21½° W.,
106 lks. dist., with scribe marks T33S R7W RS33
CC BT visible on open blaze.

A chinquapin snag, 6 ins. diam., bears N. 27° W.,
34½ lks. dist., with scribe marks T32S R7W S34
RS33 CC BT visible on open blaze.

and a bearing tree mkd. by John M. Powell, Deputy County
Surveyor, in 1968

A fir, 9 ins. diam., bears S. 34° W., 36 lks.
dist., with healed blaze.

From this point, the closing cor. of secs. 3 and 4,
established by Norman D. Price, Registered Land Surveyor
No. 33, in 1954, bears N. 0° 05' E., 0.08 chs. dist.,
monumented with an iron pipe, 2 ins. diam., firmly set,
projecting 6 ins. above ground, with brass washer mkd.
RS 33, from which the remains of bearing trees mkd. by
Price:

A fir, 42 ins. diam., bears S. 47¼° E., 85 lks.
dist., with healed blaze.

A chinquapin snag, 11 ins. diam., bears S. 20° W.,
114 lks. dist., with scribe marks T33S R7W S4
RS33 CC BT visible on open blaze.

A chinquapin snag, 6 ins. diam., bears N. 35° W.,
27½ lks. dist., with scribe marks T32S R7W S34
RS33 CC BT visible on open blaze.