

16278

Dependent Resurvey, Portion of Subdivisional Lines,
T. 33 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	and a bearing tree mkd. by John M. Powell, Deputy County Surveyor, in 1968
	<p>A fir, 9 ins. diam., bears S. 28° W., 43 lks. dist., with healed blaze.</p>
	<p>This point now becomes an amended monument.</p>
	<p>From this same point, the standard cor. of secs. 33 and 34, T. 32 S., R. 7 W., bears N. 89° 59' W., 9.79 chs. dist., hereinbefore described.</p>
	<p>Land, mountainous. Soil, rocky clay with rock outcroppings. Timber, fir, pine, cedar, oak, madrone, and chinquapin; undergrowth, poison oak, ceanothus, arrowwood, hazel, chaparral, salal, and Oregon grape.</p>
	<p>To complete the survey of section 3, I return to the standard cor. of secs. 34 and 35, T. 32 S., R. 7 W., and run</p>
	<p>N. 89° 59' W., on the N. bdy. of sec. 3.</p>
9.46	<p>Point for the E 1/16 sec. cor. of sec. 3 only, T. 33 S., R. 7 W., at midpoint bet. the closing cor. of secs. 2 and 3, and the 1/4 sec. cor. of sec. 3 only.</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;"><u>E 1/16 S 3</u> 1975</p>
	<p>from which</p>
	<p>A fir, 7 ins. diam., bears S. 46° E., 245 1/2 lks. dist., mkd. E 1/16 S3 BT.</p>
	<p>No other suitable trees available within limits.</p>
29.17	<p>Point for the 1/4 sec. cor. of sec. 3 only, at midpoint longitudinally on the N. bdy. of sec. 3, T. 33 S., R. 7 W.</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;"><u>T 33 S R 7 W</u> 1/4 S 3 1975</p>
	<p>from which</p>
	<p>A maple, 11 ins. diam., bears S. 71° E., 66 lks. dist., mkd. 1/4 S3 BT.</p>
	<p>An alder, 9 ins. diam., bears S. 65° W., 19 lks. dist., mkd. 1/4 S3 BT.</p>