

134

16279

Dependent Resurvey, Portion of Subdivisional Lines,
T. 33 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

From the cor. of secs. 16, 17, 20, and 21, perpetuated and recorded by Max W. Hull, Registered Land Surveyor No. 901, in 1973, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 4 ins. above ground, with plastic cap mkd. HULL RS 901, from which the remaining original bearing tree:

A fir, 25 ins. diam., bears S. 44° E., 11 lks. dist., with fragmentary scribe marks visible on opened blaze.

and bearing trees mkd. by Hull

A madrone, 16 ins. diam., bears S. 67° E., 43 lks. dist., with scribe marks S21 RS901 BT visible on partially healed blaze.

A madrone, 10 ins. diam., bears S. 28° W., 69½ lks. dist., with scribe marks S20 RS901 BT visible on partially healed blaze.

A madrone, 12 ins. diam., bears N. 60° W., 61 lks. dist., with scribe marks S17 RS901 BT visible on partially healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over iron rod, with brass cap mkd.

T 33 S R 7 W	
S 17	S 16
S 20	S 21
1975	

from which new bearing trees

A sugar pine, 8 ins. diam., bears S. 52½° W., 50 lks. dist., mkd. T33S R7W S20 BT.

A fir, 8 ins. diam., bears N. 47½° W., 79½ lks. dist., mkd. T33S R7W S17 BT.

No suitable tree available in sec. 16.

N. 2° 40' E., bet. secs. 16 and 17.

Descend 50 ft. over NE. slope, through scattered timber and dense undergrowth.

3.20 Bottom of descent, slopes SE.; asc. 190 ft. over SE. slope.

11.10 Spur, slopes S. 50° E.; desc. 65 ft. over NE. slope.

16.90 Ravine, drains E.; asc. 70 ft. over NE. slope.

20.60 Spur, slopes NE.; asc. 230 ft. over NE. slope.

28.20 Creek, 2 lks. wide, course NE.; continue descent over steep N. slope.

38.50 Creek, 2 lks. wide, course E.; asc. 45 ft. over SE. slope.

40.30 Point for the ¼ sec. cor. of secs. 16 and 17, at proportionate distance; there is no remaining evidence of the original corner.