

18280

Dependent Resurvey, Portion of Subdivisional Lines,
T. 33 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 33 S R 7 W

¼
S 17 | S 16
1975

from which

A fir, 9 ins. diam., bears N. 23° E., 55 lks. dist., mkd. ¼ S16 BT.

A fir, 8 ins. diam., bears N. 83° W., 66 lks. dist., mkd. ¼ S17 BT.

From this point, a point established and recorded by Max W. Hull, Registered Land Surveyor No. 901, in 1973, bears West, 0.482 chs. dist., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 4 ins. above ground, with plastic cap mkd. HULL RS 901, from which bearing trees mkd. by Hull:

A madrone, 12 ins. diam., bears N. 36° E., 26½ lks. dist., with scribe marks W ¼ RS 901 BT visible on partially healed blaze.

A madrone, 17 ins. diam., bears N. 30° W., 5 lks. dist., with scribe marks W ¼ RS 901 BT visible on partially healed blaze.

Ascend 120 ft. over SE. slope.

- 43.10 Spur, slopes SE.; desc. 60 ft. over NE. slope.
- 46.70 Rocky ravine, drains S. 60° E.; asc. 125 ft. over SE. slope.
- 50.00 Spur, slopes SE.; desc. 15 ft. over NE. slope.
- 54.20 Rocky ravine, drains SE.; asc. 510 ft. over broken SE. slope.
- 68.35 Spur, slopes S. 60° E.; desc. 110 ft. over broken E. slope.
- 80.60 Point for the cor. of secs. 8, 9, 16, and 17, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 33 S R 7 W

S 8 | S 9
S 17 | S 16
1975

from which

A sugar pine, 13 ins. diam., bears N. 25° E., 10 lks. dist., mkd. T33S R7W S9 BT.

A fir, 20 ins. diam., bears S. 65° E., 86½ lks. dist., mkd. T33S R7W S16 BT.

A fir, 25 ins. diam., bears S. 1° W., 70½ lks. dist., mkd. T33S R7W S17 BT.