

Dependent Resurvey, Portion of Subdivisional Lines,
T. 33 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
	<p style="text-align: center;">T 33 S R 7 W S 7 S 8 S 18 S 17 1975</p> <p>from which new bearing trees</p> <p>A fir, 7 ins. diam., bears N. 45° E., 15½ lks. dist., mkd. T33S R7W S8 BT.</p> <p>A madrone, 8 ins. diam., bears S. 64¼° W., 24½ lks. dist., mkd. T33S R7W S18 BT.</p> <p>A fir, 23 ins. diam., bears N. 31¾° W., 120½ lks. dist., mkd. T33S R7W S7 BT.</p> <p>Deposit corner stone alongside iron post.</p> <p>N. 0° 18' E., bet. secs. 7 and 8.</p> <p>Ascend 85 ft. over SE. slope, through scattered timber and dense undergrowth.</p> <p>5.00 Spur, slopes S. 20° W.; desc. 20 ft. over NW. slope.</p> <p>7.35 Head of ravine, drains W.; asc. 150 ft. over SW. slope.</p> <p>14.00 Top of ascent, slopes W.; desc. 20 ft. over NW. slope.</p> <p>20.50 Ravine, drains SW.; asc. 425 ft. over broken SW. slope, changing to S. slope.</p> <p>39.90 The ¼ sec. cor. of secs. 7 and 8, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 7 W ¼ S 7 S 8 1966</p> <p>from which the remaining original bearing tree</p> <p>A fir, 58 ins. diam., bears S. 1° W., 467 lks. dist., mkd. ¼ S7 BT on bark blaze. (Record, 476 lks.)</p> <p>and bearing trees mkd. by Gawron, in 1966</p> <p>A live oak, 7 ins. diam., bears S. 27° E., 25 lks. dist., with scribe marks ¼ S8 BT visible on partially healed blaze.</p> <p>A fir, 20 ins. diam., bears N. 16° W., 136 lks. dist., with healed blaze.</p> <p>Land, mountainous. Soil, rocky clay. Timber, fir, pine, cedar, oak, and madrone; undergrowth, poison oak, chaparral, manzanita, ceanothus, salal, and Oregon grape.</p>
	<p>Subdivision of Section 3, T. 33 S., R. 7 W., Willamette Meridian, Oregon</p>