CHAINS	
	From the ¼ sec. cor. of secs. 3 and 10.
	N. 0° 34' W., on the N. and S. center line of sec. 3, marking and blazing the true line.
	Descend 395 ft. over NW. slope, through heavy timber and dense undergrowth.
4.80	Abandoned dirt road, 15 lks. wide, bears N. 20° E. and S. 20° W.
8.55	Abandoned ditch, bears S. 50° W. and drains E., in curve.
13.55	Perkins Creek, 10 lks. wide, course N. 70° E.; asc. 15 ft. over SE. slope.
14.70	Creek, 2 lks. wide, course S. 60° E.; asc. 200 ft. over SE. slope.
22.50	Abandoned ditch, bears N. 80° W. and drains N. 50° E., in curve.
30.10	Spur, slopes S. 60° E.; desc. 65 ft. over NE. slope.
35.85	Ravine, drains N. 80° E.; asc. 150 ft. over SE. slope.
40.68	Point for the center ¼ sec. cor. of sec. 3, at intersection with the E. and W. center line of sec. 3.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 33 S R 7 W C ¼ S 3 1975
	from which
	A sugar pine, 7 ins. diam., bears N. 86½° E., 101½ lks. dist., mkd. C ¼ S3 BT.
	A tan oak, 8 ins. diam., bears S. 52½° W., 37 lks. dist., mkd. C ¼ S3 BT.
	Ascend 80 ft. over SE. slope.
43.30	Spur, slopes S. 70° E.; asc. 75 ft. along broken E. slope.
55.00	Spur, slopes N. 70° E.; desc. 215 ft. over N. slope.
62.96	Point for the center N 1/16 sec. cor. of sec. 3.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. C N 1/16 | S 3 C 1975
	from which
	A cedar, 21 ins. diam., bears S. 22¾° E., 76½ lks. dist., mkd. CN 1/16 S3 BT.
	A fir, 6 ins. diam., bears N. 7¼° W., 9 lks. dist., mkd. CN 1/16 S3 BT.