

142

16287

Subdivision of Section 3, T. 33 S., R. 7 W.,
Willamette Meridian, Oregon

CHAINS	
	Descend 580 ft. over N. slope.
78.35	Dirt road, 20 lks. wide, bears N. 60° E. and S. 60° W.
88.15	Cow Creek, 90 lks. wide, course S. 80° W.; asc. 5 ft. over creek bank.
89.22	The ¼ sec. cor. of sec. 3 only.
19.51	<p>From the ¼ sec. cor. of secs. 2 and 3.</p> <p>S. 89° 49' W., on the E. and W. center line of sec. 3.</p> <p>Ascend 165 ft. over broken SE. slope, through heavy timber and dense undergrowth.</p> <p>Point for the center E 1/16 sec. cor. of sec. 3.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> $\begin{array}{c} \text{E } 1/16 \\ \text{C} \quad \text{S } 3 \quad \text{C} \\ 1975 \end{array}$ <p>from which</p> <p>A madrone, 10 ins. diam., bears N. 15° W., 39½ lks. dist., mkd. CE 1/16 S3 BT.</p> <p>A fir, 10 ins. diam., bears S. 54¼° W., 56 lks. dist., mkd. CE 1/16 S3 BT.</p> <p>Ascend 260 ft. over SE. slope.</p>
27.90	Abandoned ditch, bears S. 20° W. and drains N. 10° W., in curve.
39.02	The center ¼ sec. cor. of sec. 3.
78.94	Ascend 905 ft. over broken SE. slope, changing to E. slope.
	The ¼ sec. cor. of secs. 3 and 4.
22.34	<p>From the center E 1/16 sec. cor. of sec. 3.</p> <p>N. 0° 18' W., on the N. and S. center line of the NE¼ of sec. 3.</p> <p>Descend 185 ft. over broken NE. slope, through scattered timber and dense undergrowth.</p> <p>Point for the NE 1/16 sec. cor. of sec. 3, at intersection with the E. and W. center line of the NE¼ of sec. 3.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> $\begin{array}{c} \text{NE } 1/16 \text{ S } 3 \\ 1975 \end{array}$ <p>from which</p>