

Dependent Resurvey of a Portion of the South Boundary,
T. 19 S., R. 10 W., Willamette Meridian, Oregon

CHAINS

Beginning at the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

T 19 S R 10 W
S 32 | S 33
S 5 | S 4
T 20 S
1952

from which the remains of an original bearing tree

A sawed fir stump, 34 ins. diam., bears S. 79° W.,
15 lks. dist., with healed blaze. (Record,
S. 85° W.)

and the remains of bearing trees mkd. by Mensch

A decayed fir stump, 34 ins. diam., bears N. 29° E.,
33 lks. dist., no marks visible. (Record,
N. 35° E.)

A decayed alder stump, size indeterminate, bears
S. 9° E., 42 lks. dist., no marks visible.
(Record, S. 2½° E.)

and a bearing tree mkd. by Tillman

A fir, 33 ins. diam., bears S. 26° E., 101 lks.
dist., with healed blaze. (Record, S. 20° E.)

and new bearing trees

A fir, 24 ins. diam., bears N. 40° E., 53 lks.
dist., mkd. T19S R10W S33 BT.

A fir, 6 ins. diam., bears N. 30° W., 54½ lks.
dist., mkd. T19S R10W S32 BT.

No suitable trees available within limits in sec. 5.

N. 89° 26' W., bet. secs. 5 and 32, marking and blazing
the true line.

Descend 30 ft. over gentle W. slope, through heavy timber
and dense undergrowth.

0.75 Road, asphalt surfaced, 25 lks. wide, bears N. 25° E.
and S. 25° W.

1.40 Dirt road, 10 lks. wide, bears N. 15° E. and S. 15° W.

5.15 North Fork of Smith River, 150 lks. wide, course S.;
asc. 65 ft. over E. slope.

7.60 Top of river bank, bears N. and S.; desc. 10 ft. along
gentle S. slope.

12.60 Creek, 4 lks. wide, course S. 10° E.; asc. 10 ft. over
gentle E. slope.

18.40 Point for the E 1/16 sec. cor. of secs. 5 and 32.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.