

Dependent Resurvey of a Portion of the South Boundary,
T. 19 S., R. 10 W., Willamette Meridian, Oregon

CHAINS	
	Ascend 90 ft. over NE. slope.
58.85	Spur, slopes N.; desc. 35 ft. over NW. slope.
59.80	Point for the EWW 1/256 sec. cor. of secs. 5 and 32.
	Set an iron post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.
	S 32 EWW 1/256 S 5 1979
	from which
	A hemlock, 25 ins. diam., bears N. 16¾° E., 124 lks. dist., mkd. EWW 1/256 S32 BT.
	A hemlock, 18 ins. diam., bears S. 68½° E., 80 lks. dist., mkd. EWW 1/256 S5 BT.
	Descend 10 ft. over NW. slope.
60.50	Ravine, drains N. 20° E.; asc. 300 ft. over NE. slope.
68.20	Ridge, bears SE. and W.; asc. 25 ft. along ridge top.
71.20	Leave ridge, bears E. and NW.; desc. 45 ft. over SW. slope.
73.60	Point for the cor. of secs. 5, 6, 31, and 32, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 19 S R 10 W S 31 S 32 S 6 S 5 T 20 S 1979
	from which
	A fir, 16 ins. diam., bears N. 34° E., 6 lks. dist., mkd. T19S R10W S32 BT.
	A fir, 19 ins. diam., bears S. 1° E., 22 lks. dist., mkd. T20S R10W S5 BT.
	A fir, 26 ins. diam., bears S. 55° W., 31 lks. dist., mkd. T20S R10W S6 BT.
	A fir, 13 ins. diam., bears N. 24¾° W., 30 lks. dist., mkd. T19S R10W S31 BT.
	From this point, a corner established and recorded by James W. Prochnau, Registered Engineer No. 4185, in 1971, bears S. 49° 06' W., 4.39 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd. SS 1/64 S6 S5 1971 4185, from which bearing trees mkd. by Prochnau:
	A fir, 21 ins. diam., bears S. 5° E., 42 lks. dist., with healed blaze.