

322

Dependent Resurvey of a Portion of the West Boundary,
T. 19 S., R. 10 W., Willamette Meridian, Oregon

CHAINS

(Restoring the survey by Robert O. and
Charles M. Collier, U. S. Deputy Surveyors, in 1889)

From the cor. of Tps. 19 S., Rs. 10 and 11 W.

N. 0° 04' E., bet. secs. 31 and 36, marking and blazing
the true line.

Descend 425 ft. over N. slope, through heavy timber and
dense undergrowth.

12.40 Leave timber, edge bears E. and W.; thence across nearly
level open meadow.

13.30 Dirt road, 20 lks. wide, bears E. and W.

14.90 Fiddle Creek, 25 lks. wide, course W.; asc. 95 ft. over
S. slope.

16.55 Enter timber, edge bears E. and W.

19.215 The S 1/16 sec. cor. of secs. 31 and 36, established and
recorded by James W. Prochnau, Registered Land Surveyor
No. 1305, in 1979, and is accepted as the corner, monu-
mented with an iron post, 3¼ ins. diam., firmly set,
projecting 8 ins. above ground, in a stone collar, 2 ft.
base, 6 ins. high, with aluminum cap mkd.

USDA FOREST SERVICE
R 11 W | R 10 W
T 19 S S 36 | S 31
S 1/16
1979
PLS 1305

from which bearing trees mkd. by Prochnau

A fir, 13 ins. diam., bears N. 59° E., 75 lks.
dist., with scribe marks S 1/16 S31 BT visible
on open double blaze.

A fir, 10 ins. diam., bears S. 89° W., 63 lks.
dist., with scribe marks S 1/16 S36 BT visible
on open double blaze.

N. 0° 06' E., beginning new measurement.

Ascend 450 ft. over broken SW. slope.

19.035 Point established and recorded by James W. Prochnau,
Registered Land Surveyor No. 1305, in 1979, for the
witness cor. to the ¼ sec. cor. of secs. 31 and 36, monu-
mented with an aluminum post, 3¼ ins. diam., firmly set,
projecting 6 ins. above ground, in a mound of stone, 1
ft. base, to top, with aluminum cap mkd.

USDA FOREST SERVICE
W C
↑
R 11 W 1 | R 10 W
4
19S S 36 | S 31
1979
PLS 1305