

16299

Dependent Resurvey of a Portion of the West Boundary,
T. 19 S., R. 10 W., Willamette Meridian, Oregon

CHAINS	
	<p>from which bearing trees mkd. by Prochnau</p> <p>A fir, 24 ins. diam., bears N. 54° E., 8 lks. dist., with scribe marks X BT visible on open double blaze.</p> <p>A fir, 14 ins. diam., bears N. 52° W., 24 lks. dist., with scribe marks X BT visible on open double blaze.</p> <p>Witness corner is located on spur, slopes S. 80° E.</p> <p style="text-align: center;">_____</p> <p>N. 0° 07' E., beginning new measurement.</p> <p>Descend 5 ft. over steep N. slope.</p>
0.165	<p>True point for the ¼ sec. cor. of secs. 31 and 36, as determined by James W. Prochnau, Registered Land Surveyor No. 1305, in 1979, by proportionate measurement, and is accepted as the best available evidence of the position of the original corner. This point is located on near vertical exposed bedrock, where it is impracticable to establish a permanent monument.</p> <p>Descend 310 ft. over NE. slope.</p>
6.00	Ravine, drains E.; asc. 160 ft. over S. slope.
7.85	Spur, slopes E.; desc. 35 ft. over NE. slope.
9.25	Ravine, drains E.; asc. 165 ft. over S. slope.
12.50	Spur, slopes E.; desc. 110 ft. over N. slope.
14.20	Ravine, drains E.; asc. 125 ft. over broken E. slope.
19.405	<p>Point for the N 1/16 sec. cor. of secs. 31 and 36.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S 36 S 31 1979</p> <p>from which</p> <p>A fir, 25 ins. diam., bears S. 70° E., 20 lks. dist., mkd. N 1/16 S31 BT.</p> <p>A fir, 30 ins. diam., bears S. 53½° W., 37 lks. dist., mkd. N 1/16 S36 BT.</p> <p>Ascend 130 ft. over broken E. slope.</p>
23.75	Spur, slopes E.; desc. 155 ft. over broken NE. slope.
27.85	Ravine, drains S. 80° E.; asc. 300 ft. over S. slope.
34.70	Spur, slopes SE.; desc. 165 ft. over N. slope.
38.645	<p>The cor. of secs. 25, 30, 31, and 36, perpetuated and recorded by James W. Prochnau, Registered Land Surveyor No. 1305, in 1979, monumented with an aluminum post, 3½ ins. diam., firmly set, projecting 12 ins. above ground, and in a mound of stone, 3 ft. base, to top, with aluminum cap mkd.</p>