

16304

Dependent Resurvey, Portion of Subdivisional Lines,
T. 19 S., R. 10 W., Willamette Meridian, Oregon

| | |
|-----------------|---|
| CHAINS 11.90 | Spur, slopes S. 65° E.; desc. 390 ft. over broken NE. slope. |
| 15.46 | <p>From this point, a corner established and recorded by Wilford N. Haines, Registered Land Surveyor No. 239, in 1965, bears West, 2.35 chs. dist., monumented with an iron post, 1½ ins. diam., firmly set, projecting 20 ins. above ground, with brass cap mkd. RS239 T19S S31 S32 S6 S5 T20S R10W, from which the remains of bearing trees mkd. by Haines:</p> <p>A sawed fir stump, 18 ins. diam., bears N. 64½° E., 33 lks. dist., with scribe marks BT visible on partially healed blaze.</p> <p>A sawed fir stump, 40 ins. diam., bears S. 9½° E., 41 lks. dist., with scribe marks 20S R10W S5 visible on partially healed blaze.</p> <p>A sawed fir stump, 40 ins. diam., bears S. 70½° W., 89 lks. dist., no marks visible.</p> <p>A sawed fir stump, 42 ins. diam., bears N. 2° W., 38 lks. dist., no marks visible.</p> |
| 17.86 | <p>Point for the S 1/16 sec. cor. of secs. 31 and 32.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S 31 S 32 1979</p> <p>from which</p> <p>A hemlock, 29 ins. diam., bears N. 44½° E., 54 lks. dist., mkd. S 1/16 S32 BT.</p> <p>A fir, 20 ins. diam., bears N. 66½° W., 132 lks. dist., mkd. S 1/16 S31 BT.</p> <p>Descend 145 ft. over N. slope.</p> |
| 24.50 | Creek, intermittent, 2 lks. wide, course E., from SW. and W.; asc. 270 ft. over S. slope. |
| 31.25 | Top of ascent, slopes W.; desc. 20 ft. over NW. slope. |
| 34.20 | Ravine, drains W.; asc. 65 ft. over SW. slope. |
| 35.72 | <p>Point for the ¼ sec. cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone, 2½ ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 19 S R 10 W ¼ S 31 S 32 1979</p> <p>from which</p> <p>A fir, 19 ins. diam., bears S. 61° E., 33 lks. dist., mkd. ¼ S32 BT.</p> <p>A fir, 29 ins. diam., bears N. 66½° W., 49 lks. dist., mkd. ¼ S31 BT.</p> <p>Ascend 335 ft. over broken SW. slope.</p> |
| 41.90 | Gravelled road, Forest Service No. 4811, 25 lks. wide, bears S. 45° E. and W., turning SW. |
| 48.17 | Ridge, bears NE. and NW.; desc. 480 ft. over N. slope. |
| 49.75 | Dirt road, Forest Service No. 957, 15 lks. wide, bears E. and W. |