

326

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 19 S., R. 10 W., Willamette Meridian, Oregon

CHAINS 52.95	Head of ravine, drains W.; slope changes to broken NW. slope.				
67.48	Creek, 1 lk. wide, course N. 75° W.; asc. 110 ft. over SW. slope.				
70.00	Top of ascent, slopes W.; desc. 40 ft. over NW. slope.				
71.44	The cor. of secs. 29, 30, 31, and 32, determined from the remains of the original bearing trees: <p style="margin-left: 40px;">A fir, 45 ins. diam., bears S. 65½° E., 18 lks. dist., with healed blaze. (Record, S. 61° E.)</p> <p style="margin-left: 40px;">A fir snag, 25 ins. diam., bears S. 44° W., 40 lks. dist., with scribe marks R S T visible on opened blaze.</p> <p style="margin-left: 40px;">A fir, 28 ins. diam., bears N. 5° W., 47 lks. dist., with healed blaze. (Record, N. 10° W., 51 lks.)</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 2½ ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin-left: 100px;"> <table style="margin: auto;"> <tr><td>T 19 S R 10 W</td></tr> <tr><td>S 30   S 29</td></tr> <tr><td>S 31   S 32</td></tr> <tr><td>1978</td></tr> </table> </div> <p>from which new bearing trees</p> <p style="margin-left: 40px;">A fir, 36 ins. diam., bears N. 28½° E., 66 lks. dist., mkd. T19S R10W S29 BT.</p> <p style="margin-left: 40px;">A fir, 18 ins. diam., bears S. 52½° W., 80 lks. dist., mkd. T19S R10W S31 BT.</p> <p>Land, mountainous. Soil, sandy clay. Timber, fir, maple, alder, hemlock, and cascara; undergrowth, young timber, vine maple, salmonberry, salal, huckleberry, blackberry, thimbleberry, elderberry, rhododendron, and fern.</p>	T 19 S R 10 W	S 30   S 29	S 31   S 32	1978
T 19 S R 10 W					
S 30   S 29					
S 31   S 32					
1978					
	N. 65° 21' W., bet. secs. 30 and 31.				
	Descend 140 ft. over NW. slope, through heavy timber and dense undergrowth.				
2.90	Ravine, drains S. 70° W.; asc. 65 ft. over SE. slope.				
4.85	Spur, slopes S.; desc. 100 ft. over broken SW. slope.				
11.45	Ravine, drains S. 45° W.; asc. 35 ft. over SE. slope.				
12.70	Spur, slopes S. 20° W.; desc. 155 ft. over broken SW. slope.				
20.15	Creek, 3 lks. wide, course N. 65° W., turning NW., also enter logged area, edge bears same as creek; desc. 40 ft. along wandering creek bottom through dense alder.				
25.15	Enter timber, edge bears S. 65° E. and S. 20° E.				
29.80	Leave creek, course S. 75° W., from S. 65° E.; desc. 5 ft. along broken S. slope.				