

Subdivision of Section 31, T. 19 S., R. 10 W.,  
Willamette Meridian, Oregon

CHAINS	
	From the $\frac{1}{4}$ sec. cor. of secs. 6 and 31, on the S. bdy. of the Tp.
	N. $2^{\circ} 38'$ W., on the N. and S. center line of sec. 31.
	Ascend 45 ft. along E. slope, near top of spur ridge, through heavy timber and dense undergrowth.
7.75	Ridge, bears E. and W., also gravelled road, Forest Service No. 4811, 20 lks. wide, bears same as ridge; desc. 480 ft. over NE. slope.
23.12	<p>From this point, a corner established and recorded by Wilford N. Haines, Registered Land Surveyor No. 239, in 1965, bears West, 3.37 chs. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 13 ins. above ground, with brass cap mkd. RS 239 S31 T19S <math>\frac{1}{4}</math> S S6 T20S R10W, from which bearing trees mkd. by Haines:</p> <p style="padding-left: 40px;">A fir, 22 ins. diam., bears South, 7 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 27 ins. diam., bears N. <math>15^{\circ}</math> W., 56 lks. dist., with healed blaze.</p>
	Corner is located on ridge, bears S. $20^{\circ}$ E. and N. $20^{\circ}$ W., at SE. corner of logged area, edge bears N. $80^{\circ}$ W. and N. $5^{\circ}$ W.
25.61	<p>Point for the center S <math>\frac{1}{16}</math> sec. cor. of sec. 31.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>C S <math>\frac{1}{16}</math>   S 31 C 1979</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 39 ins. diam., bears East, 94 lks. dist., mkd. CS <math>\frac{1}{16}</math> S31 BT.</p> <p style="padding-left: 40px;">A cedar, 13 ins. diam., bears N. <math>4^{\circ}</math> W., 185 lks. dist., mkd. CS <math>\frac{1}{16}</math> S31 BT.</p>
	Descend 200 ft. over NE. slope.
33.85	Ravine, drains N. $65^{\circ}$ W., from East, and S. $40^{\circ}$ E.; asc. 230 ft. over SW. slope.
40.75	Spur, slopes W.; desc. 95 ft. over NW. slope.
45.40	Bottom of descent, drains W.; asc. 140 ft. over SW. slope.
49.25	Spur, slopes W.; desc. 100 ft. over N. slope.
51.22	<p>Point for the center <math>\frac{1}{4}</math> sec. cor. of sec. 31, at intersection with the E. and W. center line.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 19 S R 10 W C <math>\frac{1}{4}</math> S 31 1979.</p> </div>