

15305

Subdivision of Section 31, T. 19 S., R. 10 W.,
Willamette Meridian, Oregon

CHAINS	
	<p>from which</p> <p>An alder, 12 ins. diam., bears S. 10½° E., 67 lks. dist., mkd. C ¼ S31 BT, on bark.</p> <p>A fir, 40 ins. diam., bears N. 70° W., 104 lks. dist., mkd. C ¼ S31 BT.</p> <p>Descend 200 ft. over N. slope.</p>
56.00	Ravine, drains SW.; asc. 335 ft. over S. slope.
68.45	Ridge, bears E. and W.; desc. 60 ft. over N. slope.
69.93	Point for the center N 1/16 sec. cor. of sec. 31.
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">C N 1/16 S 31 C 1979</p>
	<p>from which</p> <p>An alder, 22 ins. diam., bears S. 74° E., 36 lks. dist., mkd. CN 1/16 S31 BT, on bark.</p> <p>A fir, 43 ins. diam., bears S. 40° W., 102 lks. dist., mkd. CN 1/16 S31 BT.</p> <p>Corner is located at east edge of logged area, edge bears N. and S.</p> <p>Descend 455 ft. over N. slope.</p>
87.15	Creek, intermittent, 5 lks. wide, course N. 65° W., also enter timber, edge bears S. and N. 65° W.; asc. 80 ft. over SW. slope.
88.64	The ¼ sec. cor. of secs. 30 and 31.
	<p>From the ¼ sec. cor. of secs. 31 and 32.</p> <p>N. 67° 19' W., on the E. and W. center line of sec. 31.</p> <p>Descend 30 ft. over SW. slope, through medium timber and dense undergrowth.</p>
1.35	Ravine, drains S.; asc. 205 ft. over SE. slope.
6.75	Gravelled road, Forest Service No. 4811, 30 lks. wide, bears NW. and NE., in curve, also spur, slopes S.; desc. 50 ft. over SW. slope.
9.50	Ravine, drains S.; asc. 75 ft. over SE. slope.
11.25	Gravelled road, Forest Service No. 4811, 30 lks. wide, bears N. 45° E. and S. 45° W.
12.25	Ridge, bears N. 45° E. and S. 45° W.; desc. 285 ft. over NW. slope.
18.20	Ravine, drains S. 55° W.; asc. 225 ft. over SE. slope.