

16307

Subdivision of Section 31, T. 19 S., R. 10 W.,
Willamette Meridian, Oregon

CHAINS	
	A fir, 20 ins. diam., bears N. $36\frac{1}{4}^{\circ}$ E., 99 lks. dist., mkd. SW 1/16 S31 BT.
	An alder, 18 ins. diam., bears N. 67° W., 30 lks. dist., mkd. SW 1/16 S31 BT, on bark.
	Descend 375 ft. over N. slope.
36.10	Dirt road, 20 lks. wide, bears E. and W.
37.10	Ravine, drains W.; asc. 95 ft. over SW. slope.
45.58	The center W 1/16 sec. cor. of sec. 31.
	From the center S 1/16 sec. cor. of sec. 31.
	N. $61^{\circ} 24'$ W., on the E. and W. center line of the SW $\frac{1}{4}$ of sec. 31.
	Ascend 95 ft. over broken NE. slope, through scattering old growth timber and dense undergrowth.
3.65	Spur, slopes N., also enter logged area, edge bears N. and S.; desc. 300 ft. over W. slope.
10.30	Ravine, drains N. 25° E.; asc. 240 ft. over E. slope.
15.75	Spur, slopes NE.; desc. 85 ft. over NW. slope.
19.00	Ravine, drains N. 50° E.; asc. 120 ft. over E. slope.
21.55	Spur, slopes N. 15° E.; desc. 75 ft. over NW. slope.
23.315	The SW 1/16 sec. cor. of sec. 31.
	Descend 85 ft. over NW. slope.
25.05	Ravine, drains N. 10° W.; asc. 35 ft. over NE. slope.
27.35	Spur, slopes N. 20° W.; desc. 160 ft. over W. slope.
30.20	Ravine, drains N.; asc. 75 ft. over NE. slope.
33.40	Spur, slopes N.; desc. 255 ft. over NW. slope.
39.60	Ravine, drains N.; asc. 30 ft. over SE. slope.
41.60	Spur, slopes N.; desc. 40 ft. over NW. slope.
43.55	Bottom of descent, slopes S., also dirt road, 20 lks. wide, bears N. 45° E. and S. 45° W.; thence across nearly level bottom land.
49.20	Fiddle Creek, 15 lks. wide, course SW.; asc. 100 ft. over SE. slope.
53.30	The S 1/16 sec. cor. of secs. 31 and 36, on the W. bdy. of the Tp.
	From the center W 1/16 sec. cor. of sec. 31.
	N. $1^{\circ} 19'$ W., on the N. and S. center line of the NW $\frac{1}{4}$ of sec. 31.
	Descend 15 ft. along broken W. slope, changing to NW. slope, through logged area, and dense brush.