

Subdivision of Section 31, T. 19 S., R. 10 W.,
Willamette Meridian, Oregon

CHAINS 18.93	<p>Point for the NW 1/16 sec. cor. of sec. 31, at intersection with the E. and W. center line of the NW¼.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S 31 1979</p> <p>from which</p> <p style="padding-left: 40px;">A maple, 18 ins. diam., bears N. 59¼° E., 46 lks. dist., mkd. NW 1/16 S31 BT.</p> <p style="padding-left: 40px;">A maple, 5 ins. diam., bears S. 8½° W., 34 lks. dist., mkd. NW 1/16 S31 BT.</p> <p>Descend 80 ft. over NW. slope.</p>
22.70	Fiddle Creek, 15 lks. wide, course S. 45° W.; asc. 5 ft. over level bottom land.
25.65	Leave bottom land, edge bears NE. and SW.; asc. 245 ft. over SE. slope.
31.85	Spur, slopes E.; desc. 130 ft. over NE. slope.
37.70	Ravine, drains S. 50° E.; asc. 10 ft. over S. slope.
37.84	The W 1/16 sec. cor. of secs. 30 and 31.
	<p>From the center N 1/16 sec. cor. of sec. 31.</p> <p>N. 66° 21' W., on the E. and W. center line of the NW¼ of sec. 31.</p> <p>Ascend 45 ft. over broken N. slope, through logged area, and dense brush.</p>
7.70	Spur, slopes N.; desc. 425 ft. over NW. slope.
21.37	The NW 1/16 sec. cor. of sec. 31.
	Descend 120 ft. over NW. slope.
24.55	Fiddle Creek, 15 lks. wide, course S.; asc. 400 ft. over E. slope.
26.83	Enter timber, edge bears N. and S.
31.25	Spur, slopes N. 80° E.; asc. 70 ft. over broken N. slope.
41.45	Spur, slopes S. 35° E.; desc. 30 ft. along S. slope.
47.20	Ravine, drains S. 40° E.; asc. 80 ft. over E. slope.
48.87	The N 1/16 sec. cor. of secs. 31 and 36, on the W. bdy. of the Tp.
	<p>GENERAL DESCRIPTION</p> <p>The lands included in the foregoing survey are located approximately 11 miles southeast of Florence, Oregon. The south and east boundaries of section 31 are the county line separating Lane and Douglas Counties.</p>