

## T. 32 S., R. 6 W., Willamette Meridian, Oregon

## CHAINS

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines, township 32 south, range 6 west, Willamette Meridian, Oregon.

The history of surveys pertaining to this resurvey, is as follows:

A portion of the subdivisional lines was surveyed by Wells Lake and George W. Hyde, in 1855.

The remaining subdivisional lines were surveyed by William H. Byars, in 1881.

A portion of the subdivisional lines was resurveyed and section 15 was subdivided by Rollin D. Aanrud, in 1966-67.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and Special Instructions dated July 13, 1976, for Group Number 910, Oregon.

The directions of the lines were determined by the solar transit method.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions, based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein. Only those lines bounding or crossing public lands were blazed. All lines not forming closures were measured twice.

The geographic position of the  $\frac{1}{4}$  section corner of sections 27 and 28, as scaled from the Canyonville, Oregon, quadrangle map, published by the United States Geological Survey, in 1954, is as follows:

Latitude  $42^{\circ} 45.7'$  N. Longitude  $123^{\circ} 24.3'$  W.

The mean magnetic declination is  $20^{\circ}$  E.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 32 S., R. 6 W., Willamette Meridian, Oregon

(Restoring the survey by Wells Lake and George W. Hyde, U. S. Deputy Surveyors, in 1855, the survey by William H. Byars, U. S. Deputy Surveyor, in 1881, and the resurvey by Rollin D. Aanrud, Cadastral Surveyor, in 1966-67)

Beginning at the  $\frac{1}{4}$  sec. cor. of secs. 27 and 28, perpetuated by G. J. Wenderoth, Deputy County Surveyor, in 1948, from original evidence no longer in existence, monumented with an iron pipe, 1 in. diam., firmly set, projecting 4 ins. above ground, from which the remains of bearing trees mkd. by Wenderoth:

A madrone, 19 ins. diam., bears S.  $25\frac{1}{2}^{\circ}$  E., 82 lks. dist., with illegible scribe marks visible on partially healed double blaze.