

Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

A root hole, bears S. 85° W., 89 lks. dist.

and a bearing tree mkd. by the Douglas County Surveyor,
in 1967

A fir, 6 ins. diam., bears N. 69½° W., 29½ lks.
dist., with healed double blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, directly over iron pipe, with brass cap
mkd.

FND. OK 1-91
M III-34

T 32 S R 6 W
S 28 | S 27
1976

Corner is located at intersection of wire fences, fences
extend N., S., E., and W.

N. 0° 41' E., bet. secs. 27 and 28, marking and blazing
the true line.

Ascend 25 ft. over SE. slope, through scattering timber
and light undergrowth, along wire fence.

6.25 Top of ascent, slopes E.; desc. 95 ft. over NE. slope.

13.90 Bottom of descent, slopes SE.; asc. 305 ft. over S.
slope, changing to SE. slope.

19.85 Corner of wire fences, fences extend N., S., and E.

20.08 From this point, a locally established corner of which I
have no record, bears East, 0.05 chs. dist., monumented
with an iron pipe, 1 in. diam., firmly set, projecting
16 ins. above ground.

40.18 Point for the cor. of secs. 21, 22, 27, and 28, at pro-
portionate distance; there is no remaining evidence of
the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

FND. OK 1-91
M III-34

T 32 S R 6 W
S 21 | S 22
S 28 | S 27
1976

from which

A fir, 9 ins. diam., bears N. 58½° E., 36 lks.
dist., mkd. T32S R6W S22 BT.

A fir, 6 ins. diam., bears S. 37° E., 56 lks.
dist., mkd. T32S R6W S27 BT.

A fir, 7 ins. diam., bears S. 64½° W., 43 lks.
dist., mkd. T32S R6W S28 BT.

A fir, 9 ins. diam., bears N. 51½° W., 42 lks.
dist., mkd. T32S R6W S21 BT.