

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 32 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	
19.90	A corner established and recorded by H. W. Lawrence, Registered Engineer No. 1543, in 1963, monumented with an iron pipe, $\frac{3}{4}$ in. diam., firmly set, projecting 11 ins. above ground, with aluminum cap mkd. S22 E 1/16 S27 1543.
19.95	Point for the E 1/16 sec. cor. of secs. 22 and 27.  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 28 ins. in the ground, with brass cap mkd.  $\begin{array}{r} \text{E } 1/16 \quad \text{S } 22 \\ \quad \quad \quad \text{S } 27 \\ \quad \quad \quad 1976 \end{array}$ from which  A yew, 17 ins. diam., bears N. $43^\circ$ E., 288 $\frac{1}{2}$ lks. dist., mkd. E 1/16 S22 BT.  A white fir, 16 ins. diam., bears S. $30\frac{1}{4}^\circ$ E., 33 $\frac{1}{2}$ lks. dist., mkd. E 1/16 S27 BT.  Descend 10 ft. over open pasture.
22.70	Wood Creek, 15 lks. wide, course S.; asc. 25 ft. over open pasture.
37.20	Wire fence, extends NE. and W.
38.50	Irrigation ditch, 5 lks. wide, course S. $30^\circ$ W., enter scattered timber and light undergrowth, edge bears NE. and SW.
39.90	Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 27, at proportionate distance; there is no remaining evidence of the original corner.  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.  $\begin{array}{r} \text{T } 32 \text{ S } \text{R } 6 \text{ W} \\ \frac{1}{4} \quad \text{S } 22 \\ \quad \quad \quad \text{S } 27 \\ \quad \quad \quad 1976 \end{array}$ from which  A cedar, 6 ins. diam., bears N. $4^\circ$ E., 28 lks. dist., mkd. $\frac{1}{4}$ S22 BT.  A white oak, 7 ins. diam., bears S. $38\frac{1}{2}^\circ$ E., 105 $\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S27 BT.  Ascend 30 ft. over SE. slope, along wire fence.
43.70	Top of ascent, slopes S.; desc. 15 ft. along S. slope.
51.90	Dry bed of creek, 5 lks. wide, course S.; asc. 70 ft. over SE. slope.
54.80	Dirt road, 15 lks. wide, bears N. $10^\circ$ W. and S. $10^\circ$ E.
55.90	Dirt road, 15 lks. wide, bears NW. and SE.
60.00	Top of ascent, slopes SE.; desc. 20 ft. over SW. slope.
65.60	Enter spring seepage, drains S.