

16315

Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	
67.40	Leave spring seepage; asc. 190 ft. over SE. slope.
70.65	Abandoned dirt road, 12 lks. wide, bears N. 10° E. and S. 10° W.
79.80	The cor. of secs. 21, 22, 27, and 28. Land, valley bottom E½ mile, rolling foothills W½ mile. Soil, clay loam. Timber, fir, pine, oak, madrone, cedar, alder, ash, and willow; undergrowth, wild blackberry, poison oak, and fir and pine reproduction.
20.095	N. 1° 38' W., bet. secs. 21 and 22. Ascend 130 ft. over SE. slope, through heavy timber and dense undergrowth. Point for the S 1/16 sec. cor. of secs. 21 and 22. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. S 1/16 S 21 S 22 1976 from which A cedar, 15 ins. diam., bears S. 77½° E., 49½ lks. dist., mkd. S 1/16 S22 BT. A cedar, 14 ins. diam., bears N. 87° W., 29½ lks. dist., mkd. S 1/16 S21 BT. Ascend 70 ft. over broken SE. slope.
24.70	Top of ascent, slopes E.; desc. 10 ft. over NE. slope.
26.20	Ravine, drains SE.; asc. 210 ft. over SE. slope.
40.19	The ¼ sec. cor. of secs. 21 and 22, determined at record bearing from the remains of the original bearing trees: A burned and decayed fir stump, 60 ins. diam., bears N. 35° E., 43 lks. dist., no marks visible. (Record, 40 lks.) A burned and decayed fir stump, 72 ins. diam., bears S. 80° W., 15 lks. dist., no marks visible. (Record, 11 lks.) At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 32 S R 6 W ¼ S 21 S 22 1976 from which new bearing trees A fir, 21 ins. diam., bears N. 80° E., 18 lks. dist., mkd. ¼ S22 BT.