

Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	
	<p>A fir, 43 ins. diam., bears N. 75° W., 72 lks. dist., mkd. ¼ S21 BT.</p> <hr/> <p>N. 0° 47' W., beginning new measurement.</p> <p>Ascend 260 ft. over SE. slope.</p>
13.70	<p>Spur, slopes E.; desc. 50 ft. over NE. slope.</p>
19.345	<p>The N 1/16 sec. cor. of secs. 21 and 22, established by person(s) unknown, and is accepted as the corner, monumented with an iron pipe, 1½ ins. diam., firmly set, projecting 12 ins. above ground.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S 21 S 22 1976</p> <p>from which</p> <p>A fir, 7 ins. diam., bears S. 52° E., 42 lks. dist., mkd. N 1/16 S22 BT.</p> <p>A fir, 32 ins. diam., bears S. 33° W., 41½ lks. dist., mkd. N 1/16 S21 BT.</p> <p>Reset iron pipe alongside iron post.</p> <hr/> <p>N. 0° 47' W., beginning new measurement.</p> <p>Descend 50 ft. over NE. slope.</p>
2.85	<p>Ravine, drains E.; asc. 515 ft. over rocky SE. slope.</p>
19.345	<p>The cor. of secs. 15, 16, 21, and 22, monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T 32 S R 6 W S 16 S 15 S 21 S 22 1966</p> <p>from which the remains of the original bearing trees</p> <p>A root hole, bears N. 89° E., 6 lks. dist.</p> <p>A root hole, bears S. 55° E., 38 lks. dist.</p> <p>A madrone clump, bears S. 43° W., 20 lks. dist.</p> <p>A root hole, bears N. 5° W., 60 lks. dist., with a down and decayed chinquapin alongside, size indeterminate, with illegible scribe marks visible on decayed blaze.</p> <p>and bearing trees mkd. by Aanrud</p> <p>A fir, 13 ins. diam., bears N. 3° E., 63 lks. dist., with healed blaze. (Record, 69 lks.)</p>