

16319

Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

FND. OK
1-91 M III - 34

T 32 S R 6 W

$$\frac{1}{2} \begin{array}{l} S 21 \\ S 28 \end{array}$$

1976

from which

A fir, 9 ins. diam., bears N. 39° W., 71½ lks. dist., mkd. ¼ S21 BT.

A fir, 15 ins. diam., bears S. 42½° E., 41½ lks. dist., mkd. ¼ S28 BT.

Descend 30 ft. over SW. slope.

43.65 Creek, 2 lks. wide, course S. 50° E.; asc. 180 ft. over E. slope.

54.30 Spur, slopes SE.; desc. 5 ft. over S. slope.

58.30 Creek, 2 lks. wide, course SE.; asc. 370 ft. over SE. slope.

74.90 Spur, slopes SE.; asc. 5 ft. along S. slope.

80.70 The cor. of secs. 20, 21, 28, and 29.

Land, mountainous.

Soil, rocky clay.

Timber, fir, pine, cedar, oak, madrone, yew, hemlock, chinquapin, and alder; undergrowth, poison oak, hazel, ceanothus, manzanita, and fir and pine reproduction.

N. 0° 21' E., bet. secs. 20 and 21.

Ascend 180 ft. over S. slope, through heavy timber and dense undergrowth.

6.30 Spur, slopes SE.; asc. 590 ft. over broken SE. slope.

32.00 Spur, slopes E.; desc. 75 ft. over NE. slope.

34.80 Ravine, drains NE.; asc. 130 ft. over SE. slope.

39.94 Point for the ¼ sec. cor. of secs. 20 and 21, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 32 S R 6 W

$$\frac{1}{2} \begin{array}{l} S 20 \\ S 21 \end{array}$$

1976

from which

A fir, 15 ins. diam., bears S. 83° E., 67 lks. dist., mkd. ¼ S21 BT.

A fir, 26 ins. diam., bears N. 10½° W., 49 lks. dist., mkd. ¼ S20 BT.