

305

15320

Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	
	Ascend 25 ft. over S. slope.
41.20	Spur, slopes E.; desc. 80 ft. over NE. slope.
48.80	Bottom of descent, slopes E.; asc. 65 ft. over SE. slope.
55.90	Ridge, bears NE. and SW., also dirt road, 15 lks. wide, bears same; desc. 450 ft. over NW. slope.
74.70	Ravine, drains W.; asc. 25 ft. over SW. slope.
77.20	Spur, slopes W.; desc. 15 ft. along W. slope.
79.88	Point for the cor. of secs. 16, 17, 20, and 21, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> T 32 S R 6 W S 17 S 16 S 20 S 21 1976 </div>
	from which
	A cedar, 38 ins. diam., bears N. 77° E., 74 lks. dist., mkd. T32S R6W S16 BT.
	A fir, 38 ins. diam., bears S. 52½° W., 66 lks. dist., mkd. T32S R6W S20 BT.
	A fir, 35 ins. diam., bears N. 42° W., 93 lks. dist., mkd. T32S R6W S17 BT.
	No suitable tree available within limits in sec. 21.
	Land, mountainous. Soil, rocky clay. Timber, fir, pine, cedar, oak, and madrone; undergrowth, poison oak, arrowwood, huckleberry, salal, and fir and pine reproduction.
	From the cor. of secs. 15, 16, 21, and 22.
	S. 89° 36' W., bet. secs. 16 and 21.
	Ascend 175 ft. over SE. slope, changing to E. slope, through heavy timber and dense undergrowth.
8.25	Spur, slopes N. 85° E.; desc. 105 ft. over broken N. slope.
20.12	Point for the E 1/16 sec. cor. of secs. 16 and 21.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> E 1/16 $\frac{S 16}{S 21}$ 1976 </div>
	from which
	A white fir, 10 ins. diam., bears N. 60° E., 82½ lks. dist., mkd. E 1/16 S16 BT.