

Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

2.80	Ravine, drains NW.; asc. 5 ft. along W. slope.
5.00	Spur, slopes W.; desc. 100 ft. over NW. slope.
7.80	Wet ravine, drains NW.; asc. 115 ft. over broken SW. slope.
12.00	Spur, slopes SW.; desc. 40 ft. over W. slope.
15.60	Bottom of descent, slopes W.; asc. 270 ft. over SW. slope.
39.95	Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 17, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 32 S R 6 W $\frac{1}{4}$ S 17 S 16 1976 </div> from which A fir, 10 ins. diam., bears N. 45° E., 47 lks. dist., mkd. $\frac{1}{4}$ S16 BT. A fir, 11 ins. diam., bears N. 16° W., 60 lks. dist., mkd. $\frac{1}{4}$ S17 BT. Ascend 140 ft. over SW. slope.
49.20	Ridge, bears NW. and SE.; desc. 575 ft. over NE. slope.
71.00	Creek, 1 lk. wide, course N. 10° E.; desc. 120 ft. over NE. slope.
78.80	Creek, 2 lks. wide, course E.; asc. 70 ft. over SE. slope.
79.90	The cor. of secs. 8, 9, 16, and 17, perpetuated and recorded by the Douglas County Surveyor, in 1959, monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd. <div style="text-align: center;"> S 8 S 9 S 17 S 16 T 32 S R 6 W 1959 </div> from which the remains of the original bearing trees A root hole, bears N. 55° E., 68 lks. dist., with a down fir alongside, 10 ins. diam., with illegible scribe marks visible on opened blaze. A fir, 20 ins. diam., bears S. 38° E., 15 lks. dist., with healed double blaze. A sawed fir stump, 29 ins. diam., bears N. 5° W., 82 lks. dist., with illegible scribe marks visible on opened upper blaze and healed lower blaze. and bearing trees mkd. by the County Surveyor